SkyGloss

SEAL

Professional Application Guide

Achieve enhanced hydrophobicity and long-lasting protection by following these precise application steps for SkyGloss SEAL. This sprayable hydrophobic sealant is primarily used as a post-application enhancer for FUSION but can also hydrate and reactivate any coatings in the SkyGloss lineup.

Preparation – Set the Stage for Perfection

1. Ensure Vehicle is Clean and Free from Contamination

- If applying after FUSION, wait at least 12 hours before proceeding.
- Thoroughly wash the vehicle to remove all dirt, grease, and debris.

2. Remove Residue if Necessary

- If any wax, silicone, or other residues are present, strip them off using a degreasing agent.
- The surface must be completely clean for optimal bonding and performance.
- Clean surface with IPA before application if needed.

3. Ideal Working Conditions

- Apply indoors or in a controlled, dust-free environment.
- Avoid direct sunlight, wind, or high humidity.
- Ensure the engine is cool — heat from a running engine can affect leveling and curing.

Apply SEAL

1. Shake the bottle well before use.
2. Spray a liberal amount of SEAL directly onto a section of the vehicle
3. Using 2 clean microfibers, with the first microfiber spread around and work into the panel, with the second microfiber, wipe dry with a until clear and streak-free.
4. Continue section-by-section until the entire vehicle is treated.

You've now completed the **SkyGloss SEAL application** — enhancing hydrophobicity and revitalizing your SkyGloss coating for superior water-repellency and shine.

Aftercare

SEAL can be applied whenever hydrophobicity and sleekness is lost.

SKYGLOSS, INC. 21575 N 11TH PL, UNIT 120, PHOENIX, AZ 85024 UNITED STATES. 602 705 3343. INFO@SKYGLOSS.COM. SKYGLOSS.COM