<>

圓

Files, Part 1: Working with files

Alex Kizer edited this page on Apr 6 · 6 revisions

We've already seen open and fopen (todo link here) so let's look at some more advanced concepts.

How do I tell how large a file is?

For files less than the size of a long using fseek and ftell is a simple way to accomplish this:

Move to the end of the file and find out the current position.

```
fseek(f, 0, SEEK_END);
long pos = ftell(f);
```

This tells us the current position in the file in bytes - i.e. the length of the file!

fseek can also be used to set the absolute position.

```
fseek(f, 0, SEEK_SET); // Move to the start of the file
fseek(f, posn, SEEK_SET); // Move to 'posn' in the file.
```


All future reads and writes in the parent or child processes will honor this position. Note writing or reading from the file will change the current position.

See the man pages for fseek and ftell for more information.

What happens if a child process closes a filestream using fclose or close?

Unlike position, closing a file stream is unique to each process. Other processes can continue to use their own file-handle.

Legal and Licensing information: Unless otherwise specified, submitted content to the wiki must be original work (including text, java code, and media) and you provide this material under a Creative Commons License. If you are not the copyright holder, please give proper attribution and credit to existing content and ensure that you have license to include the materials.



Clone this wiki locally

https://github.com/angrave/SystemPr

Clone in Desktop