

Unit 1-9 Exercises

1. Creating Two New Variables

- Retrieve the starter program **p109e01**.
- In the DATA step, create two new variables, **Increase** and **NewSalary**.
 - Increase** is the **Salary** multiplied by 0.10.
 - NewSalary** is **Salary** added with **Increase**.
- Include only the following variables: **Employee_ID**, **Salary**, **Increase**, and **NewSalary**.
- Store formats displaying commas for **Salary**, **Increase**, and **NewSalary**.
- Submit the program to create the following PROC PRINT report:

Partial PROC PRINT Output (First 10 of 424 Observations)

Obs	Employee_ID	Employee Annual	Increase	NewSalary
		Salary		
1	120101	163,040	16,304	179,344
2	120102	108,255	10,826	119,081
3	120103	87,975	8,798	96,773
4	120104	46,230	4,623	50,853
5	120105	27,110	2,711	29,821
6	120106	26,960	2,696	29,656
7	120107	30,475	3,048	33,523
8	120108	27,660	2,766	30,426
9	120109	26,495	2,650	29,145
10	120110	28,615	2,862	31,477

2. Creating Three New Variables

- Write a DATA step to read **orion.customer** to create **Work.birthday**.
- In the DATA step, create three new variables, **Bday2009**, **BdayDOW2009**, and **Age2009**.
 - Bday2009** is the combination of the month of **Birth_Date**, the day of **Birth_Date**, and the constant of 2009 in the MDY function.
 - BdayDOW2009** is the day of the week of **Bday2009**.
 - Age2009** is the age of the customer in 2009. Subtract **Birth_Date** from **Bday2009** and then divide by 365.25.
- Include only the following variables: **Customer_Name**, **Birth_Date**, **Bday2009**, **BdayDOW2009**, and **Age2009**.
- Format **Bday2009** to resemble a two-digit day, a three-letter month, and a four-digit year. **Age2009** should be formatted to appear with no digits after the decimal point.

- e. Write a PROC PRINT step to create the following report:

Partial PROC PRINT Output (First 10 of 77 Observations)

Obs	Customer_Name	Birth_	Bday2009	Bday	Age2009
		Date		DOW2009	
1	James Kvarniq	27JUN1974	27JUN2009	7	35
2	Sandrina Stephano	09JUL1979	09JUL2009	5	30
3	Cornelia Krah1	27FEB1974	27FEB2009	6	35
4	Karen Ballinger	18OCT1984	18OCT2009	1	25
5	Elke Wallstab	16AUG1974	16AUG2009	1	35
6	David Black	12APR1969	12APR2009	1	40
7	Markus Sepke	21JUL1988	21JUL2009	3	21
8	Ulrich Heyde	16JAN1939	16JAN2009	6	70
9	Jimmie Evans	17AUG1954	17AUG2009	2	55
10	Tonie Asmussen	02FEB1954	02FEB2009	2	55

3. Using the CATX and INTCK Functions to Create Variables

- a. Write a DATA step to read **orion.sales** to create **Work.employees**.

- b. In the DATA step, create the new variable **FullName**, which is the combination of **First_Name**, a space, and **Last_Name**. Use the CATX function.



Documentation on the CATX function can be found in the SAS Help and Documentation from the Contents tab ([SAS Products](#) ⇒ [Base SAS](#) ⇒ [SAS 9.3 Language Reference: Dictionary](#) ⇒ [Dictionary of Language Elements](#) ⇒ [Functions and CALL Routines](#) ⇒ [CATX Function](#)).

- c. In the DATA step, create the new variable **Yrs2012**, which is the number of years between January 1, 2012, and **Hire_Date**. Use the INTCK function.



Documentation on the INTCK function can be found in the SAS Help and Documentation from the Contents tab ([SAS Products](#) ⇒ [Base SAS](#) ⇒ [SAS 9.3 Language Reference: Dictionary](#) ⇒ [Dictionary of Language Elements](#) ⇒ [Functions and CALL Routines](#) ⇒ [INTCK Function](#)).

- d. Format **Hire_Date** to resemble a two-digit day, a two-digit month, and a four-digit year.
- e. Give **Yrs2012** a label of **Years of Employment in 2012**.

- f. Write a PROC PRINT step with a VAR statement to create the following report:

Partial PROC PRINT Output (First 10 of 165 Observations)

Obs	FullName	Hire_Date	Years of Employment in 2012
1	Tom Zhou	01/06/1989	23
2	Wilson Dawes	01/01/1974	38
3	Irenie Elvish	01/01/1974	38
4	Christina Ngan	01/07/1978	34
5	Kimiko Hotstone	01/10/1985	27
6	Lucian Daymond	01/03/1979	33
7	Fong Hofmeister	01/03/1979	33
8	Satyakam Denny	01/08/2006	6
9	Sharryn Clarkson	01/11/1998	14
10	Monica Kletschkus	01/11/2006	6

4. Creating Variables Conditionally

- a. Retrieve the starter program **p109e04**.
- b. In the DATA step, create three new variables, **Discount**, **DiscountType**, and **Region**.

If **Country** is equal to CA or US,

- **Discount** is equal to 0.10
- **DiscountType** is equal to Required
- **Region** is equal to North America.

If **Country** is equal to any other value,

- **Discount** is equal to 0.05
- **DiscountType** is equal to Optional
- **Region** is equal to Not North America.

- c. Include only the following variables: **Supplier_Name**, **Country**, **Discount**, **DiscountType**, and **Region**.
- d. Submit the program to create the following PROC PRINT report:

Partial PROC PRINT Output (First 10 of 52 Observations)

Obs	Supplier_Name	Country	Region	Discount	Discount Type
1	Scandinavian Clothing A/S	NO	Not North America	0.05	Optional
2	Petterson AB	SE	Not North America	0.05	Optional
3	Prime Sports Ltd	GB	Not North America	0.05	Optional
4	Top Sports	DK	Not North America	0.05	Optional
5	AllSeasons Outdoor Clothing	US	North America	0.10	Required
6	Sportico	ES	Not North America	0.05	Optional
7	British Sports Ltd	GB	Not North America	0.05	Optional
8	Eclipse Inc	US	North America	0.10	Required
9	Magnifico Sports	PT	Not North America	0.05	Optional
10	Pro Sportswear Inc	US	North America	0.10	Required

5. Creating Variables Unconditionally and Conditionally

- a. Write a DATA step to read **orion.orders** to create **Work.ordertype**.
- b. Create the new variable **DayOfWeek**, which is equal to the week day of **Order_Date**.
- c. Create the new variable **Type**, which is equal to
 - Catalog Sale if **Order_Type** is equal to 1
 - Internet Sale if **Order_Type** is equal to 2
 - Retail Sale if **Order_Type** is equal to 3.
- d. Create the new variable **SaleAds**, which is equal to
 - Mail if **Order_Type** is equal to 1
 - Email if **Order_Type** is equal to 2.
- e. Do not include **Order_Type**, **Employee_ID**, and **Customer_ID**.
- f. Write a PROC PRINT step to create the following report:

Partial PROC PRINT Output (First 20 of 490 Observations)

Obs	Order_ID	Order_ Date	Delivery_ Date	Type	Sale Ads	Day Of Week
1	1230058123	11JAN2003	11JAN2003	Catalog Sale	Mail	7
2	1230080101	15JAN2003	19JAN2003	Internet Sale	Email	4
3	1230106883	20JAN2003	22JAN2003	Internet Sale	Email	2
4	1230147441	28JAN2003	28JAN2003	Catalog Sale	Mail	3
5	1230315085	27FEB2003	27FEB2003	Catalog Sale	Mail	5
6	1230333319	02MAR2003	03MAR2003	Internet Sale	Email	1
7	1230338566	03MAR2003	08MAR2003	Internet Sale	Email	2
8	1230371142	09MAR2003	11MAR2003	Internet Sale	Email	1
9	1230404278	15MAR2003	15MAR2003	Catalog Sale	Mail	7
10	1230440481	22MAR2003	22MAR2003	Catalog Sale	Mail	7
11	1230450371	24MAR2003	26MAR2003	Internet Sale	Email	2
12	1230453723	24MAR2003	25MAR2003	Internet Sale	Email	2
13	1230455630	25MAR2003	25MAR2003	Catalog Sale	Mail	3
14	1230478006	28MAR2003	30MAR2003	Internet Sale	Email	6
15	1230498538	01APR2003	01APR2003	Catalog Sale	Mail	3
16	1230500669	02APR2003	03APR2003	Retail Sale		4
17	1230503155	02APR2003	03APR2003	Internet Sale	Email	4
18	1230591673	18APR2003	23APR2003	Internet Sale	Email	6
19	1230591675	18APR2003	20APR2003	Retail Sale		6
20	1230591684	18APR2003	18APR2003	Catalog Sale	Mail	6

6. Using WHEN Statements in a SELECT Group to Create Variables Conditionally

- Write a DATA step to read **orion.nonsales** to create **Work.gifts**.
- Create two new variables, **Gift1** and **Gift2**, using a SELECT group with WHEN statements.

If **Gender** is equal to F,

- **Gift1** is equal to Perfume
- **Gift2** is equal to Cookware.

If **Gender** is equal to M,

- **Gift1** is equal to Cologne
- **Gift2** is equal to Lawn Equipment.

If **Gender** is not equal to F or M,

- **Gift1** is equal to Coffee
- **Gift2** is equal to Calendar.



Documentation on the SELECT group with WHEN statements can be found in the SAS Help and Documentation from the Contents tab ([SAS Products](#) ⇒ [Base SAS](#) ⇒ [SAS 9.3 Language Reference: Dictionary](#) ⇒ [Dictionary of Language Elements](#) ⇒ [Statements](#) ⇒ [SELECT Statement](#)).

- Include only the following variables: **Employee_ID**, **First**, **Last**, **Gift1**, and **Gift2**.
- Write a PROC PRINT step to create the following report:

Partial PROC PRINT Output (First 15 of 235 Observations)

Obs	Employee_ID	First	Last	Gift1	Gift2
1	120101	Patrick	Lu	Cologne	Lawn Equipment
2	120104	Kareen	Billington	Perfume	Cookware
3	120105	Liz	Povey	Perfume	Cookware
4	120106	John	Hornsey	Cologne	Lawn Equipment
5	120107	Sherie	Sheedy	Perfume	Cookware
6	120108	Gladys	Gromek	Perfume	Cookware
7	120108	Gabriele	Baker	Perfume	Cookware
8	120110	Dennis	Entwisle	Cologne	Lawn Equipment
9	120111	Ubaldo	Spillane	Cologne	Lawn Equipment
10	120112	Ellis	Glattback	Perfume	Cookware
11	120113	Riu	Horsey	Perfume	Cookware
12	120114	Jeannette	Buddery	Coffee	Calendar
13	120115	Hugh	Nichollas	Cologne	Lawn Equipment
14	.	Austen	Ralston	Cologne	Lawn Equipment
15	120117	Bill	Mccleary	Cologne	Lawn Equipment

7. Subsetting Observations Based on Two Conditions

- Retrieve the starter program **p109e07**.
- In the DATA step, write a statement to select only the observations that have **Emp_Hire_Date** greater than or equal to July 1, 2006. Subset the observations as they are being read into the program data vector.
- In the DATA step, write another statement to select only the observations that have an increase greater than 3000.
- Submit the program to create the following PROC PRINT report:

Obs	Employee ID	Employee Annual Salary	Employee Hire Date	Increase	NewSalary
1	120128	30,890	01NOV2006	3,089	33,979
2	120144	30,265	01OCT2006	3,027	33,292
3	120161	30,785	01OCT2006	3,079	33,864
4	120264	37,510	01DEC2006	3,751	41,261
5	120761	30,960	01JUL2006	3,096	34,056
6	120995	34,850	01AUG2006	3,485	38,335
7	121055	30,185	01AUG2006	3,019	33,204
8	121062	30,305	01AUG2006	3,031	33,336
9	121085	32,235	01JAN2007	3,224	35,459
10	121107	31,380	01JUL2006	3,138	34,518

8. Subsetting Observations Based on Three Conditions

- Write a DATA step to read **orion.orders** to create **Work.delays**.
- Create the new variable **Order_Month**, which is equal to the month of **Order_Date**.
- Use a WHERE statement and a subsetting IF statement to select only the observations that meet all of the following conditions:
 - Delivery_Date** values that are more than four days beyond **Order_Date**
 - Employee_ID** values that are equal to 99999999
 - Order_Month** values occurring in August
- Write a PROC PRINT step to create the following report:

Obs	Order_ID	Order_ Type	Employee_ID	Customer_ID	Order_ Date	Delivery_ Date	Order_ Month
1	1231227910	2	99999999	70187	13AUG2003	18AUG2003	8
2	1231270767	3	99999999	52	20AUG2003	26AUG2003	8
3	1231305521	2	99999999	16	27AUG2003	04SEP2003	8
4	1231317443	2	99999999	61	29AUG2003	03SEP2003	8
5	1233484749	3	99999999	2550	10AUG2004	15AUG2004	8
6	1233514453	3	99999999	70201	15AUG2004	20AUG2004	8
7	1236673732	3	99999999	9	10AUG2005	15AUG2005	8
8	1240051245	3	99999999	71	30AUG2006	05SEP2006	8
9	1243165497	3	99999999	70201	24AUG2007	29AUG2007	8

9. Using an IF-THEN DELETE Statement to Subset Observations

- a. Write a DATA step to read `orion.employee_donations` to create `Work.bigdonations`.
- b. Create the new variable `Total`, which is equal to the sum of `Qtr1`, `Qtr2`, `Qtr3`, and `Qtr4`.
- c. Create the new variable `NoDonation`, which is equal to the count of missing values in `Qtr1`, `Qtr2`, `Qtr3`, and `Qtr4`. Use the NMISS function.



Documentation on the NMISS function can be found in the SAS Help and Documentation from the Contents tab ([SAS Products](#) ⇒ [Base SAS](#) ⇒ [SAS 9.3 Language Reference: Dictionary](#) ⇒ [Dictionary of Language Elements](#) ⇒ [Functions and CALL Routines](#) ⇒ [NMISS Function](#)).

- d. The final data set should contain only observations meeting the following two conditions:

- `Total` values greater than or equal to 50
- `NoDonation` values equal to 0.

Use an IF-THEN DELETE statement to eliminate the observations where the conditions are not met.



The IF-THEN DELETE statement is mentioned at the end of this section in a self-study section.

- e. Write a PROC PRINT step with a VAR statement to create the following report:

Partial PROC PRINT Output (First 7 of 50 Observations)

Obs	Employee_ID	Qtr1	Qtr2	Qtr3	Qtr4	Total	No Donation
1	120267	15	15	15	15	60	0
2	120269	20	20	20	20	80	0
3	120271	20	20	20	20	80	0
4	120275	15	15	15	15	60	0
5	120660	25	25	25	25	100	0
6	120669	15	15	15	15	60	0
7	120671	20	20	20	20	80	0