

Invoice No.	
Bill of Lading	733398
Customer No.	5812
Customer P.O.	1811328

NUCOR-YAMATO STEEL CO.
P.O. BOX 1228: BLYTHEVILLE, AR 72316

CERTIFIED MILL TEST REPORT	
100% Melted and Manufactured in U.S.A	
All Shapes produced by Nucor-Yamato Steel are cast and rolled to a fully killed and fine grain practice	
Date	01/11/2026

CONTECH ENGINEERED SOLUTIONS
19060 COUNTY ROAD 66
C/O TEAM TRK ZTS=02-810-00
GILL CO 80631
USA

CONTECH ENGINEERED SOLUTIONS
19060 COUNTY ROAD 66
C/O TEAM TRK ZTS=02-810-00
GILL CO 80631
USA

ASTM A588/A588M-19 GRADE B
ASTM A709/A709M-21 GR50WT TypeB(345WT)
ASTM A6/A6M-22

Item#	Item Description	QTY	Heat#	Mechanical Properties								Chemical Properties															
				Yield to Tensile Ratio	Yield Strength	Tensile Strength	ELONG	Charpy Impact				C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb	Sn	CE	Pcm	Cl	
					KSI	KSI	%	° F	ft• lbf		Loc																
					MPa	MPa	%	° C	J																		
1	W30X090.0 50 ft 0 in W760X134 (15.24 m)	1	600784	0.77 0.77	61 60 419 411	79 77 542 533	24 24	40 4	105 142	91 123	96 130	Fla	.07	1.26	.018	.025	.26	.27	.26	.53	.03	.04	.001	.01	.44	.19	6.4
2	W30X090.0 50 ft 0 in W760X134 (15.24 m)	1	616184	0.75 0.76	58 59 402 407	78 78 537 537	24 24	40 4	56 76	51 69	50 68	Fla	.07	1.30	.013	.019	.26	.28	.34	.46	.04	.04	.001	.01	.43	.19	6.4
3	W30X090.0 50 ft 0 in W760X134 (15.24 m)	1	619185	0.79 0.79	60 60 415 417	76 77 524 529	25 25	40 4	96 130	78 106	91 123	Fla	.07	1.26	.011	.015	.30	.29	.30	.42	.04	.04	.003	.01	.42	.19	6.4
4	W30X090.0 50 ft 0 in W760X134 (15.24 m)	3	619186	0.72 0.78	58 60 397 415	80 77 549 530	24 25	40 4	120 163	124 168	120 163	Fla	.07	1.26	.012	.013	.26	.29	.32	.42	.05	.04	.001	.01	.43	.19	6.4

ELONGATION BASED ON 8.00 INCH GAUGE LENGTH

Pcm= C+Si/30+Mn/20+Cu/20+Ni/60+Cr/20+Mo/15+V/10+5B(B=Approx .0005)

Corrosion Index= 26.01(%Cu)+3.88(%Ni)+1.2(%Cr)+1.49(%Si)+17.28(%P)-7.29(%Cu)(%Ni)-9.10(%Ni)(%P)-33.39(%Cu)^2

ISO 9001:2015 certified (Registration # 0985-07).

Meets mechanical lab independence requirements of EN10204 type 3.1.

The Charpy machine striker geometry used by Nucor-Yamato Steel is the 8 mm (0.315") striker (KV_g) per ASTM A370 Section 22.1.2 and ISO 148-1 Section 7.3.

CARBON EQUIVALENT CE= C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15

Mercury has not been used in the direct manufacturing of this material

Boron has not been intentionally added and will not exceed 0.0008%

This material was produced in accordance with the Nucor-Yamato Steel Quality Manual.

I hereby certify that the contents of this report are accurate and correct. All test results and operations performed by this material manufacturer are in compliance with the requirements of the material specifications, and when designated by the purchaser, meet the applicable specifications.

Evan
Chief Metallurgist

State of Arkansas
County of Mississippi
Sworn to and subscribed before me
on 2026-01-11

REVIEWED

AMANDA STOCKMAN
NOTARY PUBLIC - ARKANSAS
My Comm. # 12-007936
My Comm. Expires 06/30/2034

01.30.2026