



TRU-FIT PRODUCTS • TRU-WELD

QUALITY WELD STUDS, STUD WELDING EQUIPMENT AND FASTENERS SINCE 1928

Atlanta • Calgary • Chicago • Dallas • Denver • Houston • Kansas City • Las Vegas • Medina
New York City • Salt Lake City • Smithville • Toronto • Vancouver

460 Lake Rd Medina, OH 44256 USA

Phone: (330)725-7741 Fax: (330)725-0161 Toll Free: (800)321-5588

CONTECH ENGINEERED SOLUTIONS LLC
19060 COUNTY ROAD

SC14-083-11

SC 7/8 X 5-3/16 HEADED WELD STUD B/W

GREELEY CO 80631-9664

PO NUMBER	SHIPMENT NUMBER	ORDER NUMBER	CERT DATE	CERT QUANTITY
1912615	5116425	65132373	4/22/2026	1
CERTIFICATION				

This is to certify that this product has been manufactured to conform to: STANDARD AASHTO M169 / BS EN ISO 13918/AWS D1.1-25/D1.5-25 subclause 9.9 manufacturer weld base qualification (s). Specifications of material conforming to ASTM A108-18/ A29-23, ASTM A1044/A1044M-22a, BS EN 10204 3.1, S235 JRC, BS EN10025 low carbon steel, CSA W59-18 APPENDIX H AND CSA S6-19 CLAUSE 10.4.7. having the following chemical composition and physical properties:

LOT NUMBER: 393824169
HEAT NUMBER: 20930030
GRADE: C1015
MATERIAL ORIGIN DOMESTIC (USA)
CHEMICAL COMPOSITION
CARBON: 0.150 %
MANGANESE: 0.530 %
PHOSPHORUS: 0.011 %
SULPHUR: 0.005 %
NICKEL 0.040 %
CHROMIUM 0.090 %
MOLYBDENUM 0.020 %
ALUMINUM 0.028 %
SILICON 0.240 %
COPPER 0.080 %
BORON 0.0002 %
CEV 0.27 %

MECHANICAL PROPERTIES

REFERENCE	TW24-228 1	TW24-228 2
ULTIMATE	66,786 PSI 460 N/mm ²	69,352 PSI 478 N/mm ²
YIELD (0.2% OFFSET)	54,382 PSI 374 N/mm ²	55,314 PSI 381 N/mm ²
REDUCTION OF AREA	64.1 %	65.8 %
ELONGATION	39.1 %	39.1 %

BEND TEST	PASSED	PASSED
FAILURE LOCATION	SHANK	SHANK

Mechanical properties above are derived from finished product using ASTM A370 testing procedures. TFP Corporation certifies that this is a copy of the original mechanical certification on file, that this product is melted and manufactured in the U.S.A., is free from mercury contamination and is free from repair welding.

By: Samuel T Ray

Samuel T Ray
Q.A. Manager
Tru-Weld Division
TFP Corporation