

AIRPORT INDUSTRIAL PARK
685 AVIATION BOULEVARD
GEORGETOWN, SC 29440



TELEPHONE: (843) 546-1044
FAX: (843) 546-1055
E-MAIL: sales@con-servinc.com
engineering@con-servinc.com

SERVICE • QUALITY • ECONOMY

CERTIFICATION OF COMPLIANCE

DATE: February 3, 2026

SOLD TO: CONTECH ENGINEERED SOLUTIONS
SALES ORDER NUMBER: 226-1346
CUSTOMER PURCHASE ORDER NUMBER: 1856403
ITEMS: PREFORMED FABRIC PADS


QTY: (4) 1 X 4 X 8

We hereby certify that the preformed fabric pad shall comply with the AASHTO specification DIV. II SECT. 18 PARA .18.10.2

The preformed fabric pads shall be composed of multiple layers of 8 oz. cotton duck impregnated and bound with high-quality natural rubber or of equivalent and equally suitable materials compressed into resilient pads of uniform thickness. The number of plies shall be such as to produce the specified thickness, after compression and vulcanizing. The finished pads shall withstand compression loads perpendicular to the plane of the laminations of not less than 10,000 pounds per square inch without detrimental reduction in thickness or extrusion. The pad also shall comply with MIL-C-882-E Military Specification.

All materials manufactured in the U. S. A.

CON-SERV INCORPORATED

A handwritten signature in black ink, appearing to read "Ricky Eldreth", is written over a horizontal line.

RICKY ELDTRETH
QUALITY CONTROL MANAGER



Steel Dynamics Sales North America, Inc.
4500 County Rd 59
Butler, IN 46721 USA
Telephone (260) 868-8000

Metallurgical Certification

Cert # 3840738

Ship To	Truck Collect - T	Contact			
	Butler, IN 46721 United States				
Sold To	A588 & A572 Steel Company 1401 Meadow Craft Road	Contact Bill Carmody			
	Center Point, AL 35215 United States	P: 866-968-5063 F: 1-423-968-5073			
Length	2,029 ft. / 618 m	Width	48.0000 in. / 1,219 mm	Chem Treat	No
Weight	43,720 lbs / 19,831.04 kg	Gauge	0.1270 in. / 3.23 mm Min	Oiled	No

Coil #	21B740808	Coil Alias	
Order #	726501	Heat #	42144830
Line Item #	3	PO #	32770 - 3
Part #			
Alt Part #			
Material Spec.	ASTM A 606 TYPE 4 - 18		
Product Desc.	Prime Hot Rolled Band		
Cert Comment	For conversion to ASTM A588 A&B and A242		
Surface Treatment			

Ladle Chemical Analysis (%)

C	Mn	P	S	Si	Al	Cu	Ni	Cr	Mo	Sn	N	v	Nb	Ti	B	Ca	Pb	Zr
0.05	0.84	0.016	0.004	0.41	0.023	0.32	0.19	0.44	0.02	0.009	0.009	0.038	0.002	0.001	0.0004	0.002	0.000	0.0007

Mechanical Properties (if applicable)

Sample 1	English	Metric
Sample Direction	Longitudinal	
Yield Strength	67.3 KSI	464 MPa
Tensile Strength	77.5 KSI	535 MPa
Percent Elongation	28 %	


Kyle Vanover
Metallurgist

Shipped from Butler, IN, USA

Melted, thin slab cast and rolled by proud Americans in Butler, IN, USA.

SDI does not weld or repair Prime Hot Rolled Band products.

All tests were performed according to applicable standards and are correct as contained in the records of the company.