

COMP9024: Data Structures and Algorithms

Week 1: Abstract Data Types and Pointers

1

Contents

- Abstract Data Types
- Compilation and Makefiles
- Pointers

2

Abstract Data Types (1/4)

- A data type is a set of values, and a set of operations on those values
- An ADT (Abstract Data Type) is a mathematical model for data types
 - An approach to implementing data types
 - Separates interface from implementation
- Users of an ADT see only the interface
- Builders of the ADT provide an implementation

3

Abstract Data Types (2/4)

An ADT interface provides

- a user-view of the data structure
- function signatures (prototypes) for all operations
- semantics of operations (via documentation)
- \Rightarrow a "contract" between ADT and its clients

An ADT implementation gives

- the concrete definition of the data structure
- function implementations for all operations

4

Abstract Data Types (3/4)

ADT interfaces are opaque

- Clients cannot see the implementation via the interface

ADTs are important because ...

- facilitate decomposition of complex programs
- make implementation changes invisible to clients
- improve readability and structuring

5

Abstract Data Types (4/4)

Typical operations with ADTs

- create a value of the type
- modify one variable of the type
- combine two values of the type

6

Collection ADTs (1/4)

A collection consist of a group of items where each item may be a simple type or an ADT.

Items are typically of the same type and often have a key (to identify them)


Collections may be categorised by ...

- structure:
 - linear (array, linked list), branching (tree), cyclic (graph)
- usage:
 - matrix, stack, queue, set, search-tree, dictionary, map, ...

7

Collections (2/4)


Collection structures:



8

Collections (3/4)

- Or even a hybrid structure like:



9

Collection (4/4)

For a given collection type

- many different data representations are possible

For a given operation and data representation

- several different algorithms are possible
- efficiency of algorithms may vary widely

Generally,

- there is no overall "best" representation/implementation
- cost depends on the mix of operations
(e.g. proportion of inserts, searches, deletions, ...)

10

Stack ADT (1/2)


A stack is an abstract data type that serves as a collection of elements, with the following operations:

- `createStack()`, which creates an empty stack.
- `push(element)`, which adds an element to the collection, and
- `pop()`, which removes the top element from the stack.
- `peek()`, which returns the top element without modifying the stack.
- `isEmpty()`, which checks if the stack is empty.

Elements come off a stack following LIFO (Last In First Out) order.

11

Stack ADT (2/2)



[https://en.wikipedia.org/wiki/Stack_\(abstract_data_type\)](https://en.wikipedia.org/wiki/Stack_(abstract_data_type))

12

An Implementation of Stack (1/3)

Implementation issues:

- A data structure to store all the elements
 - Different data structures (array, linked lists, ...) can be used
- A stack pointer to point to the stack top

Note that there is a hardware stack in each processor, and the processor provides

- `push` and `pop` instructions, and
- a register serving as a stack pointer

13

An Implementation of Stack (2/3)

Interface (a file named `Stack.h`)

```
// Stack header file
```

```
void stackInit();  
int isEmpty();  
void push(char);  
char pop();
```

14

An Implementation of Stack (3/3)

```
#include "Stack.h"

#define MAXITEMS 10
static struct {
    char item[MAXITEMS];
    int top;
} stackObject;

void stackInit() {
    stackObject.top = -1;
}

int isEmpty() {
    return (stackObject.top < 0);
}

void push(char ch) {
    assert(stackObject.top < MAXITEMS-1);
    stackObject.top++;
    int i = stackObject.top;
    stackObject.item[i] = ch;
}

char pop() {
    assert(stackObject.top > -1);
    int i = stackObject.top;
    char ch = stackObject.item[i];
    stackObject.top--;
    return ch;
}
```

15

Applications of Stacks

- Direct applications
 - Page-visited history in a Web browser
 - Undo sequence in a text editor
 - Chain of method calls in the Java Virtual Machine
- Indirect applications
 - Auxiliary data structure for algorithms
 - Component of other data structures

16

Bracket Matching (1/5)

Check whether all opening brackets such as '(', '[', '{' have matching closing brackets ')', ']', '}'

Which of the following expressions are correct?

1. $(a+b) * c$
2. $a[i]+b[j]*c[k])$
3. $(a[i]+b[j])*c[k]$
4. $a(a+b)*c$
5. `void f(char a[], int n) {int i; for(i=0;i<n;i++) { a[i] = (a[i]*a[i])*(i+1); }}`
6. $a(a+b * c$

-
1. Correct
 2. Not correct (case 1: an opening bracket is missing)
 3. Correct
 4. Not correct (case 2: closing bracket doesn't match opening bracket)
 5. Correct
 6. Not correct (case 3: missing closing bracket)

17

Bracket Matching (2/5)

Algorithm

```
#include "Stack.h"
```

```
bracketMatching(s) :  
|   Input   stream s of characters  
|   Output TRUE if parentheses in s balanced, FALSE otherwise  
|  
|   for each ch in s do  
| |   if ch = open bracket then  
| | |   push ch onto stack  
| |   else if ch = closing bracket then  
| | |   if stack is empty then  
| | | |   return FALSE  
| | |   else  
| | | |   pop top of stack  
| | | |   if brackets do not match then  
| | | | |   return FALSE  
| | | |   end if  
| | |   end if  
| |   end if  
|   end for  
|   if stack is not empty then return FALSE
```

18

Bracket Matching (3/5)

Execution trace of client on sample input:

([{ }])

Next char	Stack	Check
-	empty	-
((-
[([-
{	([{	-
}	([{ vs } ✓
]	([vs] ✓
)	empty	(vs) ✓
eof	empty	-

19

Bracket Matching (4/5)

Trace the algorithm on the input

```
void f(char a[], int n) {  
    int i;  
    for(i=0;i<n;i++) { a[i] = a[i]*a[i]]*(i+1); }  
}
```

20

Bracket Matching (5/5)

Next bracket	Stack	Check
start	empty	-
((-
[([-
]	(✓
)	empty	✓
{	{	-
({(-
)	{	✓
{	{{	-
[{{[-
]	{{	✓
[{{[-
]	{{	✓
[{{[-
]	{{	✓
)	{	FALSE

21

Queue ADT (1/4)

A queue consists of a linear sequence of an arbitrary number of items with the following major operations:

- **enqueue(element)**: add a new element at the end of the queue
- **dequeue()**: remove the element at the front of the queue
- Other auxiliary operations:
 - **front()**: returns the element at the front without removing it
 - **size()**: returns the number of elements stored
 - **isEmpty()**: indicates whether no elements are stored

All the elements are removed from the queue following FIFO (First In First Out) order.

22

Queue ADT (2/4)

<i>Operation</i>		<i>Output</i>	<i>Q</i>
enqueue(5)		—	(5)
enqueue(3)		—	(5, 3)
dequeue()	5	(3)	
enqueue(7)		—	(3, 7)
dequeue()	3	(7)	
front()		7	(7)
dequeue()	7	()	
dequeue()	"error"	()	
isEmpty()		true	()
enqueue(9)		—	(9)
enqueue(7)		—	(9, 7)
size()		2	(9, 7)
enqueue(3)		—	(9, 7, 3)
enqueue(5)		—	(9, 7, 3, 5)
dequeue()	9	(7, 3, 5)	

23

Queue ADT (3/4)

Applications of queues

- Direct applications
- Waiting lists, bureaucracy
- Access to shared resources (e.g., printer)
- Multiprogramming
- Indirect applications
- Auxiliary data structure for algorithms
- Component of other data structures

24

Queue ADT (4/4)

- A queue can be implemented using an array or a linked list
- Two variables keep track of the front and rear

25


Compilation and Makefiles (1/7)

Compilers are programs that

- convert program source code to executable form
- "executable" might be machine code or bytecode

The Gnu C compiler (**gcc**)

- applies source-to-source transformation (pre-processor)
- compiles *source code* to produce *object files*
- links object files and *libraries* to produce *executables*



26

Compilation and Makefiles (2/7)

Compilation/linking with gcc:

```
gcc -c Stack.c
```

```
gcc -c bracket.c
```

```
gcc -o rbt bracket.o Stack.o
```

gcc is a multi-purpose tool

- compiles (-c), links, makes executables (-o)

27

Compilation and Makefiles (3/7)

Compilation process is complex for large systems.

How much to compile?

- Ideally, what's changed since last compile
- Practically, recompile everything, to be sure

The `make` command assists by allowing

- programmers to document dependencies in code
- minimal re-compilation, based on dependencies

28

Compilation and Makefiles (4/7)

Example: multi-module program

```
main.c
#include <stdio.h>
#include "world.h"
#include "graphics.h"

int main(void)
{
    ...
    drawPlayer(p);
    spin(...);
}

world.h
typedef ... Ob;
typedef ... Pl;
extern addObject(Ob);
extern removeObject(Ob);
extern movePlayer(Pl);

graphics.h
extern drawObject(Ob);
extern drawPlayer(Pl);
extern spin(...);

world.c
#include <stdlib.h>

addObject(...)
{ ... }

removeObject(...)
{ ... }

movePlayer(...)
{ ... }

graphics.c
#include <stdio.h>
#include "world.h"

drawObject(Ob o);
{ ... }

drawPlayer(Pl p)
{ ... }

spin(...)
{ ... }
```

29

Compilation and Makefiles (5/7)

make is driven by dependencies given in a Makefile

A dependency specifies

target : source1 source2 ...

commands to build target from sources

e.g.

game : main.o graphics.o world.o

gcc -o game main.o graphics.o world.o

Rule: target is rebuilt if older than any *source*

30

Compilation and Makefiles (6/7)

A Makefile for the example program:

```
game : main.o graphics.o world.o
    gcc -o game main.o graphics.o world.o
```

```
main.o : main.c graphics.h world.h
    gcc -Wall -Werror -c main.c
```

```
graphics.o : graphics.c world.h
    gcc -Wall -Werror -c graphics.c
```

```
world.o : world.c
    gcc -Wall -Werror -c world.c
```

Things to note:

- A target (game, main.o, ...) is on a newline
 - followed by a :
 - then followed by the files that the target is dependent on
- The action (gcc ...) is always on a newline
 - and must be indented with a TAB

31

Compilation and Makefiles (7/7)

If make arguments are targets, build just those targets:

```
prompt$ make world.o
gcc -Wall -Werror -c world.c
```

If no args, build first target in the Makefile.

```
prompt$ make
gcc -Wall -Werror -c main.c
gcc -Wall -Werror -c graphics.c
gcc -Wall -Werror -c world.c
gcc -o game main.o graphics.o world.o
```

32

Memory (1/3)

Computer memory ... large array of consecutive data cells or bytes


- `char ... 1 byte` `int, float ... 4 bytes` `double ... 8 bytes`

When a variable is declared, the operating system finds a place in memory to store the appropriate number of bytes.

If we declare a variable called `k` ...

- the place where `k` is stored is denoted by `&k`
- also called the address of `k`

It is convenient to print memory addresses in Hexadecimal notation



33

Memory (2/3)

Example:

```
int k;
```

```
int m;
```

```
printf("address of k is %p\n", &k);
```

```
printf("address of m is %p\n", &m);
```

```
// address of k is BFFFFB80
```

```
// address of m is BFFFFB84
```

This means that

- `k` occupies the four bytes from `BFFFFB80` to `BFFFFB83`
- `m` occupies the four bytes from `BFFFFB84` to `BFFFFB87`

Note the use of `%p` as placeholder for an address ("pointer" value)

34

Memory (3/3)

When an array is declared, the elements of the array are stored in consecutive memory locations:

```
int array[5];

for (i = 0; i < 5; i++) {
    printf("address of array[%d] is %p\n", i, &array[i]);
}
// address of array[0] is BFFFFB60
// address of array[1] is BFFFFB64
// address of array[2] is BFFFFB68
// address of array[3] is BFFFFB6C
// address of array[4] is BFFFFB70
```

35

Pointers (1/4)

A pointer ...

- is a special type of variable
- storing the **address** (memory location) of another variable

A pointer occupies space in memory, just like any other variable of a certain type

The number of memory cells needed for a pointer depends on the computer's architecture:


- Old computer, or hand-held device with only 64KB of addressable memory:
 - 2 memory cells (i.e. 16 bits) to hold any address from 0x0000 to 0xFFFF (= 65535)
 - Desktop machine with 4GB of addressable memory
 - 4 memory cells (i.e. 32 bits) to hold any address from 0x00000000 to 0xFFFFFFFF (= 4294967295)
 - Modern 64-bit computer
 - 8 memory cells (can address 2^{64} bytes, but in practice the amount of memory is limited by the CPU)
-

36

Pointers (2/4)

Suppose we have a pointer `p` that "points to" a `char` variable `c`.

Assuming that the pointer `p` requires 2 bytes to store the address of `c`, here is what the memory map might look like:



37

Pointers (3/4)

Now that we have assigned to `p` the address of variable `c` ...

- need to be able to reference the data in that memory location

Operator `*` is used to access the object the pointer points to

- e.g. to change the value of `c` using the pointer `p`:

```
*p = 'T';
```

The `*` operator is sometimes described as "*dereferencing*" the pointer, to access the underlying variable

38

Pointers (4/4)

Things to note:

- all pointers constrained to point to a particular type of object
-
- `char *s;`
-
-
- `int *p;`

if pointer `p` is pointing to an integer variable `x`

⇒ `*p` can occur in any context that `x` could

39

Examples of Pointers (1/5)

```
int *p; int *q;
```

```
int a[5];
```

```
int x = 10, y;
```

```
p = &x;
```

```
*p = 20;
```

```
y = *p;
```

```
p = &a[2];
```

```
q = p;
```

40

Examples of Pointers (2/5)

What is the output of the following program?

```
1  #include <stdio.h>
2
3  int main(void) {
4      int *ptr1, *ptr2;
5      int i = 10, j = 20;
6
7      ptr1 = &i;
8      ptr2 = &j;
9
10     *ptr1 = *ptr1 + *ptr2;
11     ptr2 = ptr1;
12     *ptr2 = 2 * (*ptr2);
13     printf("Val = %d\n", *ptr1 + *ptr2);
14     return 0;
15 }
```

Val = 120

41

Examples of Pointers (3/5)

Can we write a function to "swap" two variables?

The *wrong* way:

```
void swap(int a, int b) {
    int temp = a;
    a = b;
    b = temp;
}

int main(void) {
    int a = 5, b = 7;
    swap(a, b);
    printf("a = %d, b = %d\n", a, b);
    return 0;
}
```

42

Examples of Pointers (4/5)

Recall that in C, scalar parameters are passed "by-value"

- Changes made to the value of a parameter do not affect the original
- Function `swap()` tries to swap the values of `a` and `b`, but fails because it only swaps the copies, not the "real" variables in `main()`

We can achieve "simulated call-by-reference" by passing pointers as parameters

43

Examples of Pointers (5/5)

Can we write a function to "swap" two variables?

The *right* way:

```
void swap(int *p, int *q) {
    int temp = *p;
    *p = *q;
    *q = temp;
}

int main(void) {
    int a = 5, b = 7;
    swap(&a, &b);
    printf("a = %d, b = %d\n", a, b);
    return 0;
}
```

44

Pointers and Arrays (1/3)

An alternative approach to iteration through an array:

- determine the **address of the first element** in the array
- determine the **address of the last element** in the array
- set a pointer variable to refer to the first element
- use **pointer arithmetic** to move from element to element
- terminate loop when address exceeds that of last element

Example:

```
int a[6];
int *p = &a[0];
while (p <= &a[5]) {
    printf("%2d ", *p);
    p++;
}
```

45

Pointers and Arrays (2/3)

Pointer-based scan written in more typical style

```
int *p;
int a[6];
for (p = &a[0]; p < &a[6]; p++)
    printf("%2d ", *p);
```

The diagram includes the following annotations:

- address of first element**: An arrow points from this text to `&a[0]` in the `for` loop.
- address of last element + 1**: An arrow points from this text to `&a[6]` in the `for` loop.
- access current element**: An arrow points from this text to `*p` in the `printf` statement.
- pointer arithmetic (move to next element)**: An arrow points from this text to `p++` in the `for` loop.

Note: because of pointer/array connection `a[i] == *(a+i)`

46

Pointers and Arrays (3/3)

argv can also be viewed as double pointer (a pointer to a pointer)

Alternative prototype for main():

```
int main(int argc, char **argv)
{
    ...
}
```

Can still use argv[0], argv[1], ...

47

Pointer Arithmetic (1/7)

A pointer variable holds a value which is an address.

C knows what type of object is being pointed to

- It knows the *sizeof* that object
- It can compute where the next/previous object is located

Example:

```
int a[6];
int *p;
p = &a[0];
p = p + 1;
```

48

Pointer Arithmetic (2/7)

For a pointer declared as `T *p;` (where `T` is a type)

- if the pointer initially contains address `A`
 - executing `p = p + k;` (where `k` is a constant)
 - changes the value in `p` to `A + k*sizeof(T)`

The value of `k` can be positive or negative.

Example:

```
int a[6];          char s[10];
int *p;             char *q;
p = &a[0];          q = &s[0];
p = p + 2;          q++;
```

49


Pointer Arithmetic (3/7)

One common type of pointer/array combination are the command line arguments

- These are 0 or more strings specified when a program is run
- If you run this command in a terminal:

prompt\$./seqq 10 20

then seqq will be given 2 command-line arguments: "10", "20"



Each element of `argv[]` is

- a pointer to the start of a character array (`char *`)
 - containing a `\0`-terminated string

50

Pointer Arithmetic (4/7)

More detail on how argv is represented:

prompt\$./seqq 5 20



51

Pointer Arithmetic (5/7)

`main()` needs different prototype if you want to access command-line arguments:

```
int main(int argc, char *argv[]) { ...
```

- `argc` ... stores the number of command-line arguments + 1
 - `argc == 1` if no command-line arguments
- `argv[]` ... stores program name + command-line arguments
 - `argv[0]` always contains the program name
 - `argv[1], argv[2], ...` are the command-line arguments if supplied

<stdlib.h> defines useful functions to convert strings:

- `atoi(char *s)` converts string to int
- `atof(char *s)` converts string to double (can also be assigned to float variable)

52

Pointer Arithmetic (6/7)

Write a program that

- checks for a single command line argument
 - if not, outputs a usage message and exits with failure
- converts this argument to a number and checks that it is positive
- applies the following Collatz's process, until 1 is reached:
 - If n is even, set n to $n/2$
 - If n is odd, set n to $3*n+1$

53

Pointer Arithmetic (7/7)

```
#include <stdio.h>
#include <stdlib.h>

void collatz(int n) {
    printf("%d\n", n);
    while (n != 1) {
        if (n % 2 == 0)
            n = n / 2;
        else
            n = 3*n + 1;
        printf("%d\n", n);
    }
}

int main(int argc, char *argv[]) {
    if (argc != 2) {
        printf("Usage: %s [number]\n", argv[0]);
        return 1;
    }
    int n = atoi(argv[1]);
    if (n > 0)
        collatz(n);
    return 0;
}
```

54

Pointers and Structures (1/3)


Like any object, we can get the address of a struct via `&`.

```
typedef char Date[11];
typedef struct {
    char name[60];
    Date birthday;
    int status;
    float salary;
} WorkerT;
WorkerT w; WorkerT *wp;
wp = &w;
*wp.salary = 125000.00;
w.salary = 125000.00;
*(wp.salary) = 125000.00;
(*wp).salary = 125000.00;
// wp->salary = 125000.00;
```

55

Pointers and Structures (2/3)

Diagram of scenario from program above:



56

Pointers and Structures (3/3)

General principle ...

If we have:

`SomeStructType s, *sp = &s;`

then the following are all equivalent:

`s.SomeElem sp->SomeElem (*sp).SomeElem`

57

Summary

- Introduction to ADTs
- Compilation and Makefiles
- Pointers
- Suggested reading:
 - introduction to ADTs ... Sedgewick, Ch.4.1-4.3
 - pointers ... Moffat, Ch.6.6-6.7

58