

Digital Image Processing ECE 566

Ahmad Ghasemi

Department of Electrical and Computer Engineering




Image Segmentation



Definition of segmentation

Partition the region R occupied by an image into R_1, \dots, R_N such that

(a) $\bigcup_{i=1}^n R_i = R.$ 

→ complete

Definition of segmentation

Partition the region R occupied by an image into R_1, \dots, R_N such that

(a) $\bigcup_{i=1}^n R_i = R.$

→ complete

(b) R_i is a connected set, for $i = 0, 1, 2, \dots, n.$

→ Points in a region connected

Definition of segmentation

Partition the region R occupied by an image into R_1, \dots, R_N such that

(a) $\bigcup_{i=1}^n R_i = R.$

→ complete

(b) R_i is a connected set, for $i = 0, 1, 2, \dots, n.$

→ Points in a region connected

(c) $R_i \cap R_j = \emptyset$ for all i and j , $i \neq j.$

→ Regions are disjoint

Definition of segmentation

Partition the region R occupied by an image into R_1, \dots, R_N such that

(a) $\bigcup_{i=1}^n R_i = R.$

→ complete

(b) R_i is a connected set, for $i = 0, 1, 2, \dots, n.$

→ Points in a region connected

(c) $R_i \cap R_j = \emptyset$ for all i and j , $i \neq j.$

→ Regions are disjoint

(d) $Q(R_i) = \text{TRUE}$ for $i = 0, 1, 2, \dots, n.$

→ Points in a region share a similarity (e. g., Same color)

Definition of segmentation

Partition the region R occupied by an image into R_1, \dots, R_N such that

(a) $\bigcup_{i=1}^n R_i = R.$

→ complete

(b) R_i is a connected set, for $i = 0, 1, 2, \dots, n.$

→ Points in a region connected

(c) $R_i \cap R_j = \emptyset$ for all i and j , $i \neq j.$

→ Regions are disjoint

(d) $Q(R_i) = \text{TRUE}$ for $i = 0, 1, 2, \dots, n.$

→ Points in a region share a similarity (e. g., Same color)










(e) $Q(R_i \cup R_j) = \text{FALSE}$ for any adjacent regions R_i and $R_j.$

→ Points from different regions are dissimilar (e. g., Different color)

Segmentation Applications

Medical imaging

- Diagnose diseases and injuries.
- Common medical imaging techniques: Radiography, MRI, ultrasound, and CT.
- Making sense of the images produced by these machines requires a lot of work. This is where image segmentation comes in.
 - Tumor detection
 - Brain segmentation
 - Diagnosis of diseases



Segmentation Applications

Autonomous vehicles

- Crucial for the proper functioning of autonomous vehicles.
- Three important types of image segmentation that enable autonomous vehicles to interpret and understand their environment
 - Object detection
 - lane segmentation
 - semantic segmentation
- Accurate image segmentation, autonomous vehicles can navigate safely and efficiently on the road.



Segmentation Applications


Agriculture

- It can help farmers improve their crop management practices, reduce production costs, and increase crop yield, ultimately leading to a more sustainable food supply.

- Estimate crop yield
- Detect weeds

<https://youtu.be/wfObVKKKJkE>

<https://www.youtube.com/watch?v=YsJ3rBhix44>



Segmentation Approaches

Edge based: boundaries of regions are different enough to allow boundary detection

Region based: partition into regions that are similar according to a criterion.

Segmentation (example): Which one is the best?

Original Image




LV




SMC



H



ED



NC




Segmentation as feature-based clustering

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 24, NO. 5, MAY 2002



Image



Scatter plot of pixel feature vectors

General Approach:

1. Assign each pixel \vec{x}_i to a “*feature vector*” $F(\vec{x}_i)$
2. Group pixels based on feature vector similarity

Assigning feature vectors to pixels

Given an image $I(\vec{x})$, consider feature vectors $\vec{F}(\vec{x})$ of the form

$$\vec{F}(\vec{x}) = \begin{pmatrix} \vec{x} \\ I(\vec{x}) \\ \vec{L}(\vec{x}) \end{pmatrix}$$

Image position

Intensity filter responses

Color filter responses

$\vec{L}(\vec{x})$ is a vector of local image features, perhaps bandpass filter responses. For color images, $\vec{F}(\vec{x})$ would also include information about the color at pixel \vec{x} .


To segment the image we might seek a clustering of the feature vectors $\vec{F}(\vec{x})$ observed in that image. A compact region of the image having a distinct gray-level or colour will correspond to a region in the feature space with a relatively high density of sampled feature vectors.

Probabilistic view of the segmentation problem

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 24, NO. 5, MAY 2002



Image




Scatter plot of pixel feature vectors

The feature vectors of pixels in a segment follow a “hidden” segment-specific distribution.

Task: To identify feature vectors arising from a same underlying distribution

Parametric vs. non-parametric methods

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 24, NO. 5, MAY 2002




Mixture of Gaussians

Parametric: Assume a specific distribution for the feature vectors and estimate its parameters

Parametric vs. non-parametric methods

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 24, NO. 5, MAY 2002




Mixture of Gaussians


Parametric: Assume a specific distribution for the feature vectors and estimate its parameters

Parametric vs. non-parametric methods

IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 24, NO. 5, MAY 2002



Mixture of Gaussians



Mean-shift segmentation

Parametric: Assume a specific distribution for the feature vectors and estimate its parameters

Non-parametric: Distribution defined implicitly using the feature vectors themselves

K-Means

- x_1, \dots, x_N are data points or vectors of observations
- Each observation (vector x_i) will be assigned to one and only one cluster
- $C(i)$ denotes cluster number for the i^{th} observation
- Dissimilarity measure: Euclidean distance metric
- K-means minimizes within-cluster point scatter:

$$W(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)=k} \|x_i - x_j\|^2 = \sum_{k=1}^K N_k \sum_{C(i)=k} \|x_i - m_k\|^2$$

where

m_k is the mean vector of the k^{th} cluster

N_k is the number of observations in k^{th} cluster

Within and Between Cluster Criteria

Let's consider total point scatter for a set of N data points:

$$T = \frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N d(x_i, x_j)$$


Distance between two points

Within and Between Cluster Criteria

Let's consider total point scatter for a set of N data points:

$$T = \frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N d(x_i, x_j)$$

Distance between two points

T can be re-written as:

$$\begin{aligned} T &= \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \left(\sum_{C(j)=k} d(x_i, x_j) + \sum_{C(j)\neq k} d(x_i, x_j) \right) \\ &= W(C) + B(C) \end{aligned}$$

Where,

$$W(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)=k} d(x_i, x_j)$$

Within cluster
scatter

$$B(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)\neq k} d(x_i, x_j)$$

Between cluster
scatter

Within and Between Cluster Criteria

Let's consider total point scatter for a set of N data points:

$$T = \frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N d(x_i, x_j)$$

Distance between two points

T can be re-written as:

$$\begin{aligned} T &= \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \left(\sum_{C(j)=k} d(x_i, x_j) + \sum_{C(j)\neq k} d(x_i, x_j) \right) \\ &= W(C) + B(C) \end{aligned}$$

Where,

$$W(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)=k} d(x_i, x_j)$$

Within cluster scatter

$$B(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)\neq k} d(x_i, x_j)$$

Between cluster scatter

If d is square Euclidean distance, then

$$W(C) = \sum_{k=1}^K N_k \sum_{C(i)=k} \|x_i - m_k\|^2$$

$$\text{and } B(C) = \sum_{k=1}^K N_k \|m_k - m\|^2$$

Grand mean

Within and Between Cluster Criteria

Let's consider total point scatter for a set of N data points:

$$T = \frac{1}{2} \sum_{i=1}^N \sum_{j=1}^N d(x_i, x_j)$$

Distance between two points

T can be re-written as:

$$\begin{aligned} T &= \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \left(\sum_{C(j)=k} d(x_i, x_j) + \sum_{C(j)\neq k} d(x_i, x_j) \right) \\ &= W(C) + B(C) \end{aligned}$$

Where,

$$W(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)=k} d(x_i, x_j)$$

Within cluster scatter

$$B(C) = \frac{1}{2} \sum_{k=1}^K \sum_{C(i)=k} \sum_{C(j)\neq k} d(x_i, x_j)$$

Between cluster scatter

If d is square Euclidean distance, then

$$W(C) = \sum_{k=1}^K N_k \sum_{C(i)=k} \|x_i - m_k\|^2$$

$$\text{and } B(C) = \sum_{k=1}^K N_k \|m_k - m\|^2$$

Grand mean

Minimizing $W(C)$ is equivalent to maximizing $B(C)$

K-Means Clustering: Expectation-Maximization

- ▶ Find values for $\{r_{nk}\}$ and $\{\mu_k\}$ to minimize:

$$J = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \|\mathbf{x}_n - \mu_k\|^2 \quad (9.1)$$

K-Means Clustering: Expectation-Maximization

- ▶ Find values for $\{r_{nk}\}$ and $\{\mu_k\}$ to minimize:

$$J = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \|\mathbf{x}_n - \mu_k\|^2 \quad (9.1)$$

- ▶ Iterative procedure:
 1. Minimize J w.r.t. r_{nk} , keep μ_k fixed ([Expectation](#))

$$r_{nk} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_n - \mu_k\|^2 \\ 0 & \text{otherwise} \end{cases} \quad (9.2)$$

K-Means Clustering: Expectation-Maximization

- ▶ Find values for $\{r_{nk}\}$ and $\{\mu_k\}$ to minimize:

$$J = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \|\mathbf{x}_n - \mu_k\|^2 \quad (9.1)$$

- ▶ Iterative procedure:

1. Minimize J w.r.t. r_{nk} , keep μ_k fixed ([Expectation](#))

$$r_{nk} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_n - \mu_k\|^2 \\ 0 & \text{otherwise} \end{cases} \quad (9.2)$$

2. Minimize J w.r.t. μ_k , keep r_{nk} fixed ([Maximization](#))

$$2 \sum_{n=1}^N r_{nk} (\mathbf{x}_n - \mu_k) = 0 \quad (9.3)$$



$$\mu_k = \frac{\sum_n r_{nk} \mathbf{x}_n}{\sum_n r_{nk}} \quad (9.4)$$

K-Means Clustering: Distortion Measure

- ▶ Dataset $\{\mathbf{x}_1, \dots, \mathbf{x}_N\}$
- ▶ Partition in K clusters
- ▶ Cluster prototype: μ_k
- ▶ Binary indicator variable, 1-of- K Coding scheme
 - $r_{nk} \in \{0, 1\}$
 - $r_{nk} = 1$, and $r_{nj} = 0$ for $j \neq k$.
 - Hard assignment.
- ▶ Distortion measure

$$J = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \|\mathbf{x}_n - \mu_k\|^2 \quad (9.1)$$

K-Means Clustering: Example



- ▶ Each E or M step reduces the value of the objective function J
- ▶ Convergence to a **global** or **local** maximum

K-Means Clustering: Choice of K


- Can $W_K(C)$, i.e., the within cluster distance as a function of K serve as any indicator?
- Note that $W_K(C)$ decreases monotonically with increasing K . That is the within cluster scatter decreases with increasing centroids.

K-Means Clustering: Choice of K


- Can $W_K(C)$, i.e., the within cluster distance as a function of K serve as any indicator?
- Note that $W_K(C)$ decreases monotonically with increasing K . That is the within cluster scatter decreases with increasing centroids.
- Instead look for elbow by using successive difference between $W_K(C)$:

$$\{W_K - W_{K+1} : K < K^*\} \gg \{W_K - W_{K+1} : K \geq K^*\}$$


K-Means Clustering: Choice of K



Data points simulated
from two pdfs



$\log(W_K)$ curve



Gap curve

$$\text{Gap}(k) = \frac{1}{B} \sum_{b=1}^B \log(W_{kb}^*) - \log(W_k)$$

This is essentially a **visual heuristic**

K-Means Clustering: Concluding Remarks

1. Direct implementation of K -Means can be slow
2. Online version:

$$\mu_k^{\text{new}} = \mu_k^{\text{old}} + \eta_n(\mathbf{x}_n - \mu_k^{\text{old}}) \quad (9.5)$$

K-Means Clustering: Concluding Remarks

1. Direct implementation of K -Means can be slow
2. Online version:

$$\mu_k^{\text{new}} = \mu_k^{\text{old}} + \eta_n(\mathbf{x}_n - \mu_k^{\text{old}}) \quad (9.5)$$

3. K -medioids, general distortion measure

$$\tilde{J} = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \mathcal{V}(\mathbf{x}_n, \mu_k) \quad (9.6)$$

where $\mathcal{V}(\cdot, \cdot)$ is any kind of dissimilarity measure

K-Means Clustering: Concluding Remarks

1. Direct implementation of K -Means can be slow
2. Online version:

$$\mu_k^{\text{new}} = \mu_k^{\text{old}} + \eta_n(\mathbf{x}_n - \mu_k^{\text{old}}) \quad (9.5)$$

3. K -medioids, general distortion measure

$$\tilde{J} = \sum_{n=1}^N \sum_{k=1}^K r_{nk} \mathcal{V}(\mathbf{x}_n, \mu_k) \quad (9.6)$$

where $\mathcal{V}(\cdot, \cdot)$ is any kind of dissimilarity measure

4. Image segmentation and compression example:



4.2 %



8.3 %



16.7 %



100 %