

---

MODULE *Chameneos*

---

A specification of a 'concurrency game' requiring concurrent and symmetrical cooperation -  
<https://cedric.cnam.fr/~chiers/RC474.pdf>

EXTENDS *Integers*

RECURSIVE *Sum*(-, -)  
 $Sum(f, S) \triangleq$  IF  $S = \{\}$  THEN 0  
ELSE LET  $x \triangleq$  CHOOSE  $x \in S$  : TRUE  
IN  $f[x] + Sum(f, S \setminus \{x\})$

---

$Color \triangleq \{\text{"blue"}, \text{"red"}, \text{"yellow"}\}$   
 $Faded \triangleq$  CHOOSE  $c : c \notin Color$

$Complement(c1, c2) \triangleq$  IF  $c1 = c2$   
THEN  $c1$   
ELSE CHOOSE  $cid \in Color \setminus \{c1, c2\}$  : TRUE

---

$N$  - number of total meeting after which *chameneoses* fade  
 $M$  - number of *chameneoses*

CONSTANT  $N, M$   
ASSUME  $N \in (Nat \setminus \{0\}) \wedge M \in (Nat \setminus \{0\})$

VARIABLE *chameneoses*, *meetingPlace*, *numMeetings*

$vars \triangleq \langle \textit{chameneoses}, \textit{meetingPlace}, \textit{numMeetings} \rangle$

$ChameneosID \triangleq 1 \dots M$   
 $MeetingPlaceEmpty \triangleq$  CHOOSE  $e : e \notin ChameneosID$

$TypeOK \triangleq$   
For each *chameneoses*, remember its current color and how many meetings it has been in.  
 $\wedge \textit{chameneoses} \in [ChameneosID \rightarrow (Color \cup \{Faded\}) \times (0 \dots N)]$   
A *meetingPlace* (called Mall in the original paper) keeps track of the *chameneoses*  
creature that is currently waiting to meet another creature.  
 $\wedge \textit{meetingPlace} \in ChameneosID \cup \{MeetingPlaceEmpty\}$

$Init \triangleq$   $\wedge \textit{chameneoses} \in [ChameneosID \rightarrow Color \times \{0\}]$   
 $\wedge \textit{meetingPlace} = MeetingPlaceEmpty$   
 $\wedge \textit{numMeetings} = 0$

$Meet(cid) \triangleq$  IF  $\textit{meetingPlace} = MeetingPlaceEmpty$   
THEN IF  $\textit{numMeetings} < N$   
chameneos enters empty meeting place  
THEN  $\wedge \textit{meetingPlace}^0 = cid$   
 $\wedge$  UNCHANGED  $\langle \textit{chameneoses}, \textit{numMeetings} \rangle$

$\text{chameneos takes on faded color}$   
 ELSE  $\wedge \text{chameneoses}^0 = [\text{chameneoses EXCEPT } ![cid] = \langle \text{Faded}, @[2] \rangle]$   
 $\wedge \text{UNCHANGED } \langle \text{meetingPlace}, \text{numMeetings} \rangle$   
 $\text{meeting place is not empty - two chameneoses mutate}$   
 ELSE  $\wedge \text{meetingPlace} \neq cid$   
 $\wedge \text{meetingPlace}^0 = \text{MeetingPlaceEmpty}$   
 $\wedge \text{chameneoses}^0 =$   
 $\text{LET } \text{newColor} \triangleq \text{Complement}(\text{chameneoses}[cid][1],$   
 $\text{chameneoses}[\text{meetingPlace}][1])$   
 $\text{IN } [\text{chameneoses EXCEPT } ![cid] = \langle \text{newColor}, @[2] + 1 \rangle,$   
 $![\text{meetingPlace}] = \langle \text{newColor}, @[2] + 1 \rangle]$   
 $\wedge \text{numMeetings}^0 = \text{numMeetings} + 1$

Repeatedly try to enter meeting place for *chameneoses* that are not faded yet.

The system terminates once the color of all *chameneoses* is faded.

$\text{Next} \triangleq \wedge \exists c \in \{x \in \text{ChameneosID} : \text{chameneoses}[x][1] \neq \text{Faded}\} : \text{Meet}(c)$

$\text{Spec} \triangleq \text{Init} \wedge \Box[\text{Next}]_{\text{vars}}$

Upon termination, the sum of the (individual) meetings that all creates have  
 been in, is equal to  $2 * N$ . It is \*not\* guaranteed that all *chameneoses* have  
 been in a meeting with another *chameneoses*. See section A. Game termination  
 on page 5 of the original papaer).

$\text{SumMet} \triangleq \text{numMeetings} = N \Rightarrow \text{LET } f[c \in \text{ChameneosID}] \triangleq \text{chameneoses}[c][2]$   
 $\text{IN } \text{Sum}(f, \text{ChameneosID}) = 2 * N$

THEOREM  $\text{Spec} \Rightarrow \Box \text{SumMet}$