

---

# **HKN CS 61A**

# **Midterm 2 Review**

---

Austin Le  
Sherdil Niyaz  
Joong Hwa Lee

---

# Hello!

---

Hosted by HKN ([hkn.eecs.berkeley.edu](http://hkn.eecs.berkeley.edu))

Office hours from 11AM to 5PM in 290 Cory, 345 Soda

Check our website for exam archive, course guide, course surveys, tutoring schedule ([hkn.eecs.berkeley.edu/tutor](http://hkn.eecs.berkeley.edu/tutor))

This is an unofficial review session and HKN is not affiliated with this course. All of the topics we are reviewing will reflect the material you have covered, our experiences in CS61A, and past midterms. We make no promise that what we cover will necessarily reflect the content of the midterm. Some members of the course staff may be presenting, but this review is *still not* official.

---

# Agenda

---

- Lists, Tuples, Dictionaries, Sequences
- Data Abstraction
- Nonlocal
- Object-Oriented Programming
- Inheritance
- Linked Lists
- Trees
- Orders of Growth

Follow along: <http://tinyurl.com/hkn-cs61a-mt2>

---

# Iterables

---


- *Lists*: Sequences that are **mutable**. We can add, remove, and change the items of a list.
  - *Tuples*: Sequences that are **immutable**. We **cannot** change the items in a tuple; we can only create new tuples.
  - *Dictionaries*: Objects that map keys to values. Remember that the keys are unordered and unique!
  - *Ranges*: Objects that represent an interval of elements between two values.
-

# Box & Pointer Diagrams

---

```
>>> l = [1, 2, 3]
```

```
>>> t = (1, 2, 3)
```




What's the difference?

# Box & Pointer Diagrams

```
>>> l = [1, 2, 3]
>>> t = (1, 2, 3)
>>> slice = l[:2]
>>> l.append(4)
```

append()  
mutates the  
original list.



Slicing creates a  
new list / tuple!

# Draw the Box & Pointer Diagram!

---

```
r = ([1, 2, 1, 2],)
```

```
s = list(r)
```

```
t = r
```

```
r[0][2] = t[0]
```

```
s[0] = r[0][1:]
```

```
s[0][1][2][3] = 4
```

# Lists : Scope

---

```
lst = [1, 2, 3, 4, 5]
def add_five(to_be_changed):
    for item in to_be_changed:
        item += 5
```

```
>> add_five(lst)
>> lst
```

What would be the result?

---



# List Comprehensions Example

---

```
>>> words = "We love CS61A!".split()
```

```
>>> words
```

```
['We', 'love', 'CS61A!']
```

```
>>> [len(w) for w in words]
```

---

```
>>> [w[i:] for w in words for i in [1, 2]]
```

---

# Dictionary Comprehensions

---

We can use list comprehension to construct dictionaries.

```
>>> d = {k : v for k, v in [(x, y) for x in range(3)  
for y in range(4)]}
```

**Remember that dictionary keys are unique!**

```
>>> d
```

```
_____
```

---

# Sequences

---

**apply\_to\_all** - Takes in a function and a sequence, and applies the function to each element of the sequence.

*Input* - Function that takes in **one argument** and any iterable sequence (list, tuple, etc.).

*Output* - Sequence of the same length as the input.

Example:

```
>>> apply_to_all(lambda x: x*x, [2, 3, 4])  
[4, 9, 16]
```

---

# Sequences

---

**reduce** - Takes in a function, a sequence and an optional initial value, and returns a single combined value. The result is accumulated as you iterate through the list.

*Input* - Function that takes in **two arguments**: an iterable sequence (list, tuple, etc.) and an (optional) starting value.

*Output* - Single element that is determined by combining the elements of the sequence using the input function.

Example:

```
>>> reduce(lambda so_far, curr: so_far+curr, [2, 3, 4])  
9
```

---

# Sequences

---

Given a list, such as [1, 2, 3, 4, 5, 6], we want to reduce the list to a single number that is the 'flattened' version of the list. For example, the output for this particular list would be the number 123456.

```
>>> from functools import reduce
>>> t = [1, 2, 3, 4, 5, 6]
>>> reduce(_____, _____)
123456
```

---

# Sequences

---

```
>>> cool = 'denero'  
>>> story = [cool[i:2*i] for i in range(6)]  
>>> story
```

---

```
>>> bro = apply_to_all(len, story)  
>>> bro
```

---

# Sequences

---

**keep\_if** - Takes in a function and a sequence, and returns a new sequence that contains only the items for which the function returns True.

*Input* - Function that takes in **one argument** which returns True or False, and any iterable sequence (list, tuple, etc.).

*Output* - Sequence that contains the elements that satisfy the function.

For example:

```
>>> keep_if(lambda x: x % 2 == 0, [2, 3, 4])  
[2, 4]
```

---

# Sequences

---

```
>>> primes = [2, 3, 5, 7, 11]
>>> fib = [0, 1, 1, 2, 3]
>>> is_prime = lambda x: x in primes
>>> apply_to_all(is_prime, keep_if(is_prime,
fib))
```

---

```
>>> get_fib = lambda x: fib[x]
>>> apply_to_all(get_fib, keep_if(is_prime,
fib))
```

---



# Data Abstraction

---

AN x64 PROCESSOR IS SCREAMING ALONG AT BILLIONS OF CYCLES PER SECOND TO RUN THE XNU KERNEL, WHICH IS FRANTICALLY WORKING THROUGH ALL THE POSIX-SPECIFIED ABSTRACTION TO CREATE THE DARWIN SYSTEM UNDERLYING OS X, WHICH IN TURN IS STRAINING ITSELF TO RUN FIREFOX AND ITS GECKO RENDERER, WHICH CREATES A FLASH OBJECT WHICH RENDERS DOZENS OF VIDEO FRAMES EVERY SECOND

BECAUSE I WANTED TO SEE A CAT JUMP INTO A BOX AND FALL OVER.



I AM A GOD.

# Data Abstraction

---

**How data is used**

**How data is  
internally  
represented**




**Abstraction Barrier**



# Data Abstraction Example: Points

---

```
def make_point(x, y):  
    return (x, y)
```



*Constructor* - Builds an object of the abstract data type.

```
def x(point):  
    return point[0]
```



*Selector* - Extracts relevant information from the object.

```
def y(point):  
    return point[1]
```

```
def dist(point1, point2):  
    return sqrt((x(point2) - x(point1)) ** 2 +  
                (y(point2) - y(point1)) ** 2)
```

# Write these functions to complete the segment data abstraction!

---

`make_segment(start, end)`

Constructs a line segment between points at start and end.

`start(segment), end(segment)`

Returns the start and end points respectively.

`length(segment)`

Returns the distance between the segment's start and end points.

`consecutive(seg1, seg2)`

Returns True if seg1's end is the same as seg2's start, or False otherwise.

For reference, the data abstraction for **points** has the following constructors and selectors:

`make_point(x, y)`

`x(point)`

`y(point)`

`dist(point1, point2)`

# Fix this!

---

Your friend has written a function to compute the total length of a path of line segments, but has broken some abstraction barriers in doing so. Rewrite this function so that it uses the line segment abstraction properly.

# Assume path is a tuple of line segments.

```
def path_length(path):
    prev = path[0][0]
    ret = dist(prev, path[0][1])
    for (s, cur) in path[1:]:
        if s != prev:
            return None
        else:
            ret += dist(s, cur)
        prev = cur
    return ret
```

---

---


**Nonlocal**

---

# Nonlocal in Environment Diagrams

```
def func1():  
    x = -100  
    def func2():  
        nonlocal x  
        x = 3  
    func2()  
func1()
```

If a variable is nonlocal, you must follow parents and look between (but not including) current frame and global.



# Nonlocal in Environment Diagrams

---

```
def func1():  
    def func2():  
        x = 4  
        def func3():  
            def func4():  
                nonlocal x  
                x = 3  
            func4()  
        func3()  
    func2()  
func1()
```

Does This Work?



# Nonlocal in Environment Diagrams

---

```
def func1():  
    def func2(x):  
        nonlocal x  
        x = 3  
    func2(4)  
func1()
```



Does This Work?

# Nonlocal in Environment Diagrams

---

```
x = 50
```

```
def func1():
```

```
    def func2():
```

```
        nonlocal x
```

```
        x = 3
```

```
    func2()
```

```
func1()
```



Does This Work?

# Draw the Environment Diagram

---

```
def k(b):  
    def seven(up):  
        b.extend(['<3', '<3'])  
        nonlocal b  
        b = 5  
        up[0][0] = 'cs61a'  
        return up[0:2]  
    return seven((b, 3, 6))
```

```
k(['cookies'])
```

---

# Environment Diagram Notes

```
def k(b):  
    def seven(up):  
        b.extend(['<3', '<3'])  
        nonlocal b  
        b = 5  
        up[0][0] = 'cs61a'  
        return up[0:2]  
    return seven((b, 3, 6))
```

Need nonlocal to  
change what  
value a variable  
points to

Don't need nonlocal  
to mutate something!


Slicing creates a  
new list with the  
same values.

```
k(['cookies'])
```

# Draw the Environment Diagram

```
def k(b):  
    def seven(up):  
        b.extend(['<3', '<3'])  
        nonlocal b  
        b = 5  
        up[0][0] = 'cs61a'  
        return up[0:2]  
    return seven((b, 3, 6))
```

`k(['cookies'])`



# Nonlocal: Domo Population

---

John Denero really likes Domos, so he buys  $n$  to start with. They multiply at the rate given by a function at every timestep. However, if the function does not increase the number of domos, use the most recent function that did. The starter function is `lambda x: x * 2`. When the number is greater than or equal to the capacity of his home, he gives 9/10 away to his beloved students. (It requires 1 timestep to give away 9/10 of the domos.)

```
def domo_population(n, capacity):  
    """  
  
    >>> timestep = domo_population(5, 40)  
    >>> timestep(lambda x: x - 10)  
    10  
    >>> timestep(lambda x: x * 4)  
    40  
    >>> timestep(lambda x: x * 3)  
    4  
    """
```

---

---

# **Object-Oriented Programming**

---

# OOP: Person

---

```
class Person(object):
    num_people = 0
    def __init__(self, name, age):
        self.name = name
        self.age = age
        Person.num_people += 1
    def has_birthday(self):
        self.age = self.age + 1
        return self.age
    def greet(self):
        return "Hi, I'm " + self.name
```

```
>>> p = Person('John Denero', 8341)
# This calls __init__.
>>> p.greet()
"Hi, I'm John Denero"
>>> p.has_birthday()
8342
>>> Person.has_birthday()
has_birthday() missing 1 required
argument: 'self'
>>> Person.has_birthday(p)
8343
>>> Person.num_people
1
>>> p.num_people
1
```

---



# OOP: Plant

```
sunny = True
class Plant:
    energy_for_leaf = 10
    def __init__(self, leaves, if_sunny=1.5, not_sunny=0.5):
        self._leaves, self.energy = leaves, 0
        self.photo_fn = lambda leaves, sunny: leaves * \
            (if_sunny if sunny else not_sunny)
    def photosynthesize(self):
        self.energy += self.photo_fn(self.leaves, sunny)
    @property
    def leaves(self):
        self.grow_leaves()
        return self._leaves
    def grow_leaves(self):
        while self.energy > self.energy_for_leaf:
            self._leaves += 1
            self.energy -= self.energy_for_leaf
    def __repr__(self):
        return 'Plant<{}, {}>'.format(self._leaves, self.energy)
```

```
>>> p = Plant(10)
>>> p # repr example
Plant<10, 0>

>>> Plant.energy_for_leaf
10
>>> p.energy_for_leaf
_____
>>> p.if_sunny
_____
>>> p.photosynthesize
_____
>>> p.photo_fn
_____
>>> p.photosynthesize()
_____
>>> p
_____
>>> p.leaves
_____
>>> p
_____
```

---

# Inheritance

---

# Inheritance: Example

---

```
class Person(object):
    def __init__(self, name, age):
        self.name = name
        self.age = age
    def has_birthday(self):
        self.age = self.age + 1
        return self.age
    def greet(self):
        return "Hi, I'm " + self.name
```

```
class Fireman(object):
    def __init__(self, name, age, fid):
        self.name = name
        self.age = age
        self.fid = fid
    def has_birthday(self):
        self.age = self.age + 1
        return self.age
    def greet(self):
        return "Hi, I'm " + self.name
    def put_out_fire(self):
        print('PUTTING OUT FIRE!')
```

# Inheritance: Example

---

```
class Person(object):
    def __init__(self, name, age):
        self.name = name
        self.age = age
    def has_birthday(self):
        self.age = self.age + 1
        return self.age
    def greet(self):
        return "Hi, I'm " + self.name
```

```
class Fireman(object):
    def __init__(self, name, age, fid):
        self.name = name
        self.age = age
        self.fid = fid
    def has_birthday(self):
        self.age = self.age + 1
        return self.age
    def greet(self):
        return "Hi, I'm " + self.name
    def put_out_fire(self):
        print('PUTTING OUT FIRE!')
```

How can we use the concept of inheritance to improve our Fireman class?

---

# Jedi

---

```
class Jedi(object):
    def __init__(self, name, lightsaber_color, ls_power):
        self.name = name
        self.ls_color = lightsaber_color
        self.ls_power = ls_power
    def lightsaber_duel(self, other_jedi):
        if self.ls_power > other_jedi.ls_power:
            print(self.name + ' defeated ' + other_jedi.name)
        elif self.ls_power == other_jedi.ls_power:
            print('Tie!')
        else:
            print(self.name + ' has fallen to ' + other_jedi.name)
```

---

# DarkJedi

---

```
class Jedi(object):
    def __init__(self, name, lightsaber_color, ls_power):
        self.name = name
        self.ls_color = lightsaber_color
        self.ls_power = ls_power
    def lightsaber_duel(self, other_jedi):
        ...

class DarkJedi(Jedi):
    def __init__(self, name, lightsaber_color, ls_power, evil_power):
        """ *** YOUR CODE HERE *** """
    def use_power(self):
        print(self.evil_power)
    def lightsaber_duel(self, other_jedi):
        """ *** YOUR CODE HERE *** """
```

---

# Facepalm

---

It is 2001 and you are a college student at Cal. You decide to create **Facepalm**, an application for the Palm Pilot that maintains information about different people in your address book.

**Facepalm** will have a **Profile** for each person. You decide to write a class called **Profile** that simulates a **Facepalm** profile. It stores a person's **name**, the person's **institution**, and a **list of Profiles** of the person's friends. It also has the `add_friend(profile)` method, which adds the given `profile` to the list of friends' Profiles, if `profile` is not already present.

---

# Facepalm - Solution

---

```
class Profile(object):  
    def __init__(self, name, inst):  
        """ YOUR CODE HERE """  
    def add_friend(self, profile):  
        """ YOUR CODE HERE """
```



# Facepalm ... with profit

---

You aren't exactly raking in the money that you were expecting from the app. To try to get some revenue, you decide that profiles will be restricted by default. A restricted profile can only add 100 friends, beyond which they are not able to add more friends. If a person tries to add more friends when they have 100 already, you should tell them to upgrade to **PaidProfiles**, which lift this restriction.

Modify `Profile.add_friend` to implement this restriction. Also define another class `PaidProfile` to mimic the `Profile` class, except in the behavior of the `add_friend` method.

---

# Facepalm ... with profit

---

```
class Profile(object):
    def __init__(self, name, inst):
        self.name = name
        self.inst = inst
        self.friends = []
    def add_friend(self, profile):
        """ YOUR CODE HERE """

class PaidProfile(Profile):
    """ YOUR CODE HERE """
```

---

## Next Topic: Linked Lists

---



# Linked Lists

---

```
class Link:
    """A linked list with a first element and the rest."""
    empty = ()
    def __init__(self, first, rest=empty):
        assert rest is Link.empty or isinstance(rest, Link)
        self.first = first
        self.rest = rest
    def __getitem__(self, i):
        if i == 0:
            return self.first
        else:
            return self.rest[i-1]
    def __len__(self):
        return 1 + len(self.rest)
```

---

# Linked Lists

---

```
class Link:
    """A linked list with a first element and the rest."""
    empty = ()
    def __init__(self, first, rest=empty):
        assert rest is Link.empty or isinstance(rest, Link)
        self.first = first
        self.rest = rest
    def __getitem__(self, i):
        if i == 0:
            return self.first
        else:
            return self.rest[i-1]
    def __len__(self):
        return 1 + len(self.rest)
```

Make an Linked List with a 2 in it?

A Linked List with 1 then 2 in it?

# Linked Lists

---

```
r = Link(1, Link(2, Link(3)))
```

How do we retrieve the 1?

Retrieve the 2?

---

# Linked Lists

---

Write reduce:

```
def reduce(lst, combiner, default):  
    """  
  
    >>> r = Link(1, Link(2, empty))  
    >>> reduce(r, lambda x, y: x + y, 0)  
    3  
    """
```

---

# Linked Lists

---

Define a procedure `skip_consecutives` that, given an Rlist of numbers, removes the consecutive duplicates with mutation.

```
def skip_consecutives(r):  
    """  
    >>> r = Link(1, Link(1, Link(3,  
                             Link(2, Link(1))))  
    >>> skip_consecutives(r)  
    # r is now Link(1, Link(3, Link(2, Link(1))))  
    """
```

---



# Linked Lists: Challenge Question

---

You have a linked list (the object-based version). What is the most efficient way to find the middle element?

---


# Next Topic: Trees

---




# Trees: Review

---



# Trees: Review

---



# Trees: Review

---

```
class Tree:
    def __init__(self, entry, branches=()):
        self.entry = entry
        for branch in branches:
            assert isinstance(branch, Tree)
        self.branches = branches

    def __repr__(self):
        if self.branches:
            return 'Tree({0}, {1})'.format(self.entry, repr(self.branches))
        else:
            return 'Tree({0})'.format(repr(self.entry))

    def is_leaf(self):
        return not self.branches
```

---

# Trees: Review

---

```
class BinTree(Tree):
    empty = Tree(None)
    empty.is_empty = True
    def __init__(self, entry, left=empty, right=empty):
        for branch in (left, right):
            assert isinstance(branch, BinTree) or branch.is_empty
        Tree.__init__(self, entry, (left, right))
        self.is_empty = False

    @property
    def left(self):
        return self.branches[0]

    @property
    def right(self):
        return self.branches[1]
```

---

# Trees: Review

---

Notice that trees are also *recursively defined*.

A tree is made from other trees –  
these trees are its *subtrees*.

Thus, a general strategy to write functions that operate  
on tree problems is *recursively*:

Apply the function on the subtrees and  
combine the results in a relevant way.

---

# Trees

---

Write a function `john_finder` that takes in a tree and returns whether it contains the string “DeNero”:

```
>>> john_finder(Tree("DeNero", (Tree("Hilfinger"))))
```

```
True
```

```
>>> john_finder(Tree("#420blazeit_6969"))
```

```
False
```

```
def john_finder(t):
```

```
    """YOUR CODE HERE"""
```

---



# Trees (Binary)

---

Write a function `tree_equals` that takes in two `BinTrees` that contain integers and returns `True` if the binary trees have the same ‘shape’ and the corresponding nodes have the same values.

```
def tree_equals(t1, t2):  
    """YOUR CODE HERE"""
```

---

# Trees

---

Write the function `prod_tree`, which takes a `Tree` of numbers and returns the product of all the numbers in the `Tree`.

```
>>> t = Tree(1, Tree(2), Tree(3, Tree(4,
                                     Tree(5),
                                     Tree(6))))
```

```
>>> prod_tree(t)
```

```
720
```

---

# Trees (Binary: HARD!)

---


Write a function `all_paths` that takes in a `BinTree` and returns a list of tuples, where each nested tuple is a path from the root to a leaf.

```
>>> all_paths(t)
[(1, 2, 3), (1, 2, 4), (1, 5, 6), (1, 5, 7)]
```

---

# Trees (Binary: HARD!)

---




```
>>> all_paths(t)
```

```
[(1, 2, 3), (1, 2, 4), (1, 5, 6), (1, 5, 7)]
```

---

# Next Topic: Orders of Growth

---



# Orders of Growth: Review

---

Way of expressing how long a function/program takes to execute in terms of the size of its input as it grows very large (given as a variable, usually  $n$ ).

Big  $\Theta$  Notation: Throw away constants in front of variable:

$$25n^2 \text{ ---> } \Theta(n^2)$$

---

# Orders of Growth

---

Keep in mind what happens as **n** grows large.

What is the order of growth for this function?

```
def func(n):  
    for i in range(n // 2):  
        print(i)  
    return n
```

# Orders of Growth

---

What is the order of growth for this function?

```
def denero(denero):  
    denero = 5 * denero  
    john = denero ** 2  
    while (john > 0):  
        print ("Announcements!")  
        john = john - 1
```

---



# Orders of Growth

---

What is the order of growth for this function?

```
def doge(n):  
    if n <= 1:  
        print ("Wow")  
        return n  
    return doge(n - 1) + doge(n - 2)
```

# Orders of Growth

---

What is the order of growth for this function?

```
def func(n):  
    if n <= 1:  
        return n  
    return 1 + func(n // 2)
```

# Orders of Growth

---

What is the order of growth for this function?

```
def func(n):  
    if n <= 1:  
        return 1  
    if n <= 50:  
        return func(n - 1) + func(n - 2)  
    elif n > 50:  
        return func(50) + func(49)
```

# Orders of Growth

---

What is the order of growth for this function?

```
def func(n):  
    lst = []  
    for i in range(n):  
        lst.append(i)  
        # Order of growth of 'append' is  $O(1)$  in the length of the list.  
    if n <= 1:  
        return 1  
    if n <= 50:  
        return func(n - 1) + func(n - 2)  
    elif n > 50:  
        return func(50) + func(49)
```

---

# Orders of Growth

---

```
def foo(x, y):  
    if x == 0:  
        return 1  
    if y > 0:  
        return foo(x, y - 1)  
    return 1 + foo(x // 2, y)
```

```
def baz(z):  
    return abs(z)
```

What is the order of growth in time for `foo(x, baz(y))` with respect to `x`?

What is the order of growth in time for `foo(x, baz(y))` with respect to `y`?

What is the order of growth in time for `foo(x, baz(y))` with respect to `x` *and* `y`?

---

# Feedback

---

We would like your feedback on this review session, so that we can improve for future review sessions. This is **completely optional**.

If you would like to provide suggestions, complaints or comments, please fill out the paper feedback form.

*Thanks for coming, and best of luck on your midterm!*

---