

HTML

Codes	Functions
<!DOCTYPE html>	- Tells the browser that this file is using HTML5. - Ensures the page displays correctly.
<html lang="en">	- Wraps the entire webpage. - lang="en" tells the browser the page is in English (good for accessibility + SEO).
<head> section	
<title>...</title>	Sets the tab name of the webpage.
<meta charset="utf-8">	Makes sure the website supports international characters like emojis, symbols, languages.
<meta name="viewport" ...>	- Ensures the website scales properly on phones, tablets, and desktops. - Makes the site responsive.
<link rel="stylesheet" href="/style.css">	Connects to the CSS file
<script src="" defer></script>	- Loads JavaScript without blocking the page. - defer improves page speed by running script after the HTML is loaded
<body>	Holds all the visible content of the webpage.
My Terrarium	Main heading of the page. Good for structure and accessibility.
<div id="page">	- A wrapper container. - Groups everything inside to control layout with CSS
<div id="left-container" class="container"> div id="right-container" class="container">	- Two containers that likely split the plants into left and right sides. - class="container" is used in CSS to style them consistently.
<div class="plant-holder">	- Wraps each plant image. - Lets you position plants neatly inside their individual boxes.
	
class="plant"	or CSS styling
id="plant1" ...	unique ID for JavaScript interactions
alt="..."	text description for accessibility or if the image fails to load
src="/images/...png"	file path of the image

CSS

Codes	Functions
<pre>body { font-family: helvetica, arial, sans-serif; }</pre>	Sets the font for the whole webpage.
<pre>h1 { color: brown; text-align: center; }</pre>	- Makes the title brown. - Centers the heading.
<pre>h1: hover { color: aqua; }</pre>	- When mouse hovers over the title, it changes to aqua. - Adds interactivity.
<pre>#left-container { background-color: #9fd6d0; width: 15%; left: 0px; top: 0px; position: absolute; height: 100%; padding: 10px; }</pre>	- Creates the left panel of the terrarium. - - Fixed on the left side using position: absolute. - - Full height (100%). - - Light blue background.responsive.
<pre>.container { background-color: burlywood; width: 15%; top: 0px; position: absolute; height: 100%; padding: 10px; }</pre>	- A general styling template for container sections. - Burlywood background. - Full-height panel. (Note: You override the background for left & right via their IDs.)
<pre>.plant-holder { position: relative; height: 13%; left: -10px; }</pre>	- Holds each plant image. - position: relative allows plant images inside to be positioned accurately. - Adjusts position slightly to the left.
<pre>.plant { position: absolute; max-width: 150%; max-height: 150%; z-index: 2; }</pre>	- Positions images inside the plant-holder. - Allows plants to be bigger than their container (up to 150%). - z-index: 2 ensures plants appear above the jar graphics.

<pre>#left-container div img { width: 50px; }</pre>	- Makes plant images smaller on the left panel. - Only affects images inside left container.
<pre>.jar-walls { height: 80%; width: 60%; background: #2eafa0; border-radius: 1rem; position: absolute; bottom: 0.5%; left: 20%; opacity: 0.5; z-index: 1; }</pre>	- Creates the main curved glass body of the jar. - Semi-transparent (opacity: 0.5). - Positioned in the center
<pre>.jar-top { width: 50%; height: 5%; background: #a8fff5; position: absolute; bottom: 80.5%; left: 25%; opacity: 0.7; z-index: 1; }</pre>	- Represents the top opening of the jar. - Positioned above the jar walls.
<pre>.jar-bottom { width: 50%; height: 1%; background: #3f615d; position: absolute; bottom: 0%; left: 25%; opacity: 0.7; }</pre>	- Small strip representing the bottom edge of the jar.
<pre>.dirt { width: 60%; height: 5%; background: #3a241d; position: absolute; border-radius: 0 0 1rem 1rem; bottom: 1%; left: 20%; opacity: 0.7; z-index: -1; }</pre>	- Brown soil at the bottom of the jar. - Behind the plants (z-index: -1).

<pre>.jar-glossy-long { width: 3%; height: 20%; border-radius: 2rem; background: #ddfbff; position: absolute; bottom: 20%; left: 5%; }</pre>	Long vertical glossy highlight on the jar wall to make it look shiny.
<pre>.jar-glossy-short { width: 3%; height: 5%; border-radius: 2rem; background: #ddfbff; position: absolute; bottom: 45%; left: 5%; }</pre>	Smaller glossy highlight to add realism.

CSS (Part 2)

Codes	Functions
<pre>@keyframes slide-in { /* animation */ 0% { transform: translateX(-100%); opacity: 0; } 100% { transform: translateX(0); opacity: 1; } } .plant { animation: slide-in 1s ease-out; }</pre>	Animation of icons when loading in
<pre>.plant { /* transition */ transition: width 0.3s, height 1s, background- color 1s; }</pre>	Transition of the icons between the starting (animation) and the ending stage (where the icons are supposed to be at)
<pre>.plant:hover { width: 200px; height: 200px; background-color: rgb(222, 240, 243); }</pre>	Similar to hover

https://www.w3schools.com/html/html_youtube.asp

<https://hookagency.com/blog/website-color-schemes/>

<https://stackoverflow.com/questions/73485179/is-there-a-way-to-add-my-own-html-and-css-files-into-github-pages-without-having>

Javascript

Document Object Model (DOM) – Represents the structure of a web page as a tree of objects. Javascript allows for interaction with the DOM to create interactivity.

Event Listeners – Functions that wait for specific events to occur and then execute code in response.

- Event Types: Clicks, key presses, and changes in the documents
- Targets: Every event is associated with a particular element in the DOM
- Event handler function: The code that should be executed when the event occurs

Closures – Allows an inner function to access variables from its outer function; useful for managing state and keeping track of data over time. Closures are also functions that remembers the variables from the place where it was created even when the function is executed.

Codes	Functions
Commands	
let	Used for most cases
const	Used if the value always stays the same
var	
Function	Allows to group instructions into a single unit that can be executed when called
	-
	-

