Options for Large-Eddy Simulations of Hurricane Boundary Layers in CM1 (and Other Numerical Models)

George Bryan

National Center for Atmospheric Research

35th Conference on Hurricanes and Tropical Meteorology New Orleans, LA 11 May 2022


Acknowledgements: NSF PREEVENTS, ONR TCRI

(also thanks to Dan Stern, Rich Rotunno, Xiaomin Chen, ...)





Large-Eddy Simulation (LES)



- Integrate governing equations using turbulence-permitting resolution
 - Δx of ~100 m or less
- Advantage:
 - A more accurate representation of turbulent processes
- Disadvantages:
 - Need to account for larger scales
 - High resolution (even Δx < 10 m) doesn't solve everything

Moeng and Sullivan (2015) (Encyclopedia of Atmospheric Sciences)

Outline

Three Options in CM1:

- 1. Small-domain, high-resolution "patch"
- 2. The "eddy recycling" method
- 3. Subgrid turbulence model

Outline

Three Options in CM1:

- 1. Small-domain, high-resolution "patch"
- 2. The "eddy recycling" method
- 3. Subgrid turbulence model

Problem:

- Hurricanes are huge! (hundreds of km)
- So, 100 m grid spacing for ~2-day simulation requires millions of supercomputer core-hours




Problem:

- Hurricanes are huge! (hundreds of km)
- So, 100 m grid spacing for ~2-day simulation requires millions of supercomputer core-hours



Solution: Simulate a "patch" of the TC boundary layer



Bryan et al. (2017a)

Bryan et al. (2017a, BLM)

radial velocity:
$$\frac{\partial u}{\partial t} = \ldots + \langle v \rangle \frac{V}{R} + \frac{\langle u \rangle^2}{R} - \left(fV + \frac{V^2}{R} \right)$$
 tangential velocity:
$$\frac{\partial v}{\partial t} = \ldots - \langle u \rangle \frac{V}{R} - \langle u \rangle \frac{\partial V}{\partial R}$$

centrifugal acceleration

- & radial advection
- & pressure-gradient acceleration

User must specify 3 terms:

- R (radius from center of TC)
- *V (z)* ("gradient wind")
- dV/dR(z) (radial gradient of V)

Caveat: applies only *outside eyewall* (r > RMW)

Chen et al. (2021, JAS)

$$\frac{\partial \theta}{\partial t} = \dots + \frac{\theta_{\text{ref}} - \langle \theta \rangle}{\tau_n}$$
$$\frac{\partial q_v}{\partial t} = \dots + \frac{q_{\text{ref}} - \langle q_v \rangle}{\tau_n}$$

These "nudging" terms account crudely for radial advection, subsidence, microphysics, radiation...

User must specify vertical profiles of θ and $q_{\scriptscriptstyle \mathcal{V}}$

CM1 default (LES Hurricane test case):

- θ : constant lapse rate
- q_v : constant relative humidity

Angled brackets: < > denotes horizontal average


Horizontal windspeed (m s⁻¹) at 100 m ASL

CM1:


 $\Delta x = \Delta y = 10 \text{ m},$ $\Delta z = 5 \text{ m}$

Input parameters:


R = 40 km $V = 38 \text{ m s}^{-1}$ $dV/dR = -8 \times 10^{-4} \text{ s}^{-1}$ (radial decay parameter n = 0.8)



Simulations (colored lines) compare well with obs. (dots)





see Bryan et al. (2017a), Chen et al. (2021, JAS) (also, the next talk!)



• simulations from Chen et al. (2021)


Nudging tendencies





Cooling and drying in lower PBL:

- Radial Advection
- Evaporation (for θ)



The Small-Domain ("patch") Hurricane LES Technique

CM₁

- Pre-configured namelists in "run/config_files"
- Since cm1r21: user settings are now in "namelist.input" file (eg, hurr_vg)
- Can rotate winds & mesoscale-tendency terms (hurr_rotate)

Other models:

- Should be easy to add
- Primarily need "mesoscale tendency terms"
 - Horizontal winds: Bryan et al. (2017a, BLM)
 - Temperature, moisture: Chen et al. (2021, JAS)
- Code to calculate domain-average profiles:
 <u>, <v>, <theta>, <qv>

Outline

Three Options in CM1:


- 1. Small-domain, high-resolution "patch"
- 2. The "eddy recycling" method
- 3. Subgrid turbulence model

Inhomogeneous Conditions


Hurricane Frances (2004)





Kosiba (2014, Hurricanes Conf.) Doppler on Wheels radial velocity: Average radial velocity 0358-0428 hr





- Not suitable for periodic lateral boundary conditions!











The "Eddy Recycling" Technique

CM₁

- Available in cm1r21.0
- See pre-configured namelists: config_files/hurricane_les_within_mm config_files/les_HurrCoast
- A work in progress; feedback welcome

Other models:


- Not easy to add…
- Need code to identify eddy "capture" and "injection" zones
- Need code to apply tendencies in "injection" zone
- Distributed-memory (MPI) communication can be a real hassle

Outline

Three Options in CM1:


- 1. Small-domain, high-resolution "patch"
- 2. The "eddy recycling" method
- 3. Subgrid turbulence model

Composites: average wind speed (uses database from Wang et al. 2015, BAMS)




see also Richter et al. (2021, JAS)


Composite wind speed from dropsondes (N = 98)



Composite wind speed from dropsondes (N = 98)



Average wind speed from CM1-LES ($\Delta x = 20 \text{ m}$)



• Overprediction of shear near surface is a common problem with LES (eg, Brasseur and Wei, 2010)

See Appendix of Bryan et al. (2017a, BLM) (motivated by Sullivan et al., 1994, BLM)

For subgrid turbulence terms

$$\frac{\partial u_i}{\partial t} = -u_j \frac{\partial u_i}{\partial x_j} - c_p \theta \frac{\partial \pi'}{\partial x_i} + \delta_{i3} g \frac{\theta'}{\theta_0} + \varepsilon_{ij3} u_j f + \frac{1}{\rho} \frac{\partial \tau_{ij}^t}{\partial x_j}$$


... add a second eddy viscosity term

$$\tau_{13}^{t} = \rho K_{m} \gamma \left(\frac{\partial u}{\partial z} + \frac{\partial w}{\partial x} \right) + \rho K_{w} \frac{\partial \widetilde{u}}{\partial z},$$


$$\tau_{23}^{t} = \rho K_{m} \gamma \left(\frac{\partial v}{\partial z} + \frac{\partial w}{\partial y} \right) + \rho K_{w} \frac{\partial \widetilde{v}}{\partial z},$$

 K_w is determined diagnostically so that <U> is logarithmic near surface (z < 100 m)

Composite wind speed from dropsondes (N = 98)



Average wind speed from CM1-LES ($\Delta x = 20 \text{ m}$)



The "Two-Part" Subgrid Turbulence Model

CM₁

- Available since cm1r20
- sgsmodel = 4
- Since cm1r21 can use time-average instead of space-average (t2p_avg = 2)
 - So we can use it for non-homogeneous cases

Other models:

- Should be fairly easy to add
- Need code to calculate average fields
 - Either spatial averages or time averages
- Code to calculate K_w is not complicated
 - (happy to share CM1 code)
- Minor addition to subgrid turbulence code

Thanks!

CM1 webpage: https://www2.mmm.ucar.edu/people/bryan/cm1 (or just google "CM1")

[These slides are now available on the CM1 webpage]

Acknowledgements: NSF PREEVENTS, ONR TCRI

(also thanks to Dan Stern, Rich Rotunno, Xiaomin Chen, ...)



