

RL-25G / RL-30G / RL-50 / RL-80G / RL-100G

Metal Separator Machine



Plastics
Machinery

Metal
Separator
Machines

01 Description

The role of metal separator for detecting and separating mixed in plastic materials of all metals, including ferrous and non-ferrous metals (such as coppers, aluminum, stainless steel). Since there will be metal impurities mixed in with them in the crushing process of recycling old material, eventually enter the production of an accident, and the increased number of maintenance shutdown, and lead to increased cost and affects the production efficiency.

02 Technical Specification

Model	RL-25G / RL-30G / RL-50 / RL-80G / RL-100G				
Voltage	220V 50/60Hz				
Working environment temp.	10~80 degree				
Material discharge speed	Free fall down				
Material discharge time	0.1-15 adjustable				
Compressed air	3-5bar		4-6bar		
Material discharge outlet size	Ø25mm	Ø30mm	Ø50mm	Ø80mm	Ø100mm
Feeding material capacity	250kg/h	300-400kg/h	700-1000kg/h	1500kg/h	2000kg/h
Detecting precision	0.3mm	0.4-0.5mm	0.5-0.6mm	0.8-0.9mm	1.0-1.1mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012