



Machine Introduction

7 inch colorful touching screen; register precision $\pm 0.05\text{mm}$, has self-diagnostic function of troubles and displays the operating pattern, 60 program units; over 6000 different cutting positions, dynamic tracking, max feeding speed 5-10m/min. It adopts import hydraulic components Japan, Korea electrical components, Taiwan ball lead screw, Its key parts adopt imported bearing of low maintenance. Feeder with double rail to ensure cutting accuracy, it adopts double enveloping worm gear reducer. IR photoelectric protection, safety device for overloading cutting, buttons by two hands safety device, main motor overloading protection for cutting.

Technical Specifications

Cutting width (cm)	115
Max. cutting height without assistance pressing plate (cm)	16
Max. cutting depth (cm)	115
Min cutting depth without assistance pressing plate (cm)	3
Extended length of working table (cm)	73
Height of working table (cm)	89
Machine width including side working table (cm)	226
Total length of working table (cm)	226
Cutting speed (r/min)	45
Max. Paper pressure (n)	40000
Power of main motor (kw)	4
Motor for paper feeding (kw)	0.75
Air pump (kw)	0.75
Machine weight (kg)	4600
Overall dimension (cm)	255x160x215

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA