

Autoprint Fine Coat 80

UV & Aqueous Coating
Machine



Machine Introduction

Autoprint is always committed to bring modern cutting edge technology to its customers. Autoprint Fine Coat 80, an offline sheet fed UV & Aqueous coating machine is one such revolutionary product from Autoprint. Autoprint Fine Coat 80 can perform full and spot (UV & Aqueous) coating on thin and thick papers at a speed of maximum 5000 sheets per hour. It is designed to meet the growing demand for a reliable and precision coater for large format printers and packaging units.

Features:

1. Stream Feeder
2. Pull Type Side Lay On Both Sides
3. Coating Unit with Anilox Roller
4. Centralized Touch Screen Control Panel
5. Varnish Pump & Duct
6. Rigid Delivery Grippers
7. Double Sheet Detector
8. Swing Arm Gripper
9. Plate Cylinder for Full/Spot Coating
10. Pneumatic Operation
11. Removable Cylinder Gripper
12. Adjustable Delivery Guides
13. Connectable to UV/IR Dryer Unit
14. Centralized Lubrication System
15. Varnish Pump / Duct

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

**34 YEARS
SERVING
INDONESIA**

Technical Specifications

Model	Autoprint Fine Coat 80
Maximum paper size	560x800 mm (22"x32")
Minimum paper size	254x304 mm (10"x12")
Maximum coating area	550x800 mm
Paper thickness	60-450 gsm
Coating speed	2000-5000 sph
Feeding system	Stream feeder
Blanket size	645x825x1.65 mm
Plate size	645x825x0.3 mm
Polymer plate thickness (for spot coating)	1.7 mm
Gripper margin on plate	40 mm
Gripper margin on paper	10 mm
Gripper bite	5 mm
Circumferential image micro adjustment	30 mm offline
Registration accuracy	± 0.5 mm
Pull lay fine adjustment	± 1.5 mm
Delivery system	Chain delivery
Varnish unit	3 Roller system
Coating thickness	3-5 gsm (adjustable)
Lubrication system	Centralized lubrication system
Power consumption	4.5 kw
Main drive motor / Compressor motor	1.5 kw (2 Hp)
Pile up / down motor, Varnish motor	0.75 kw (1 Hp), 0.374 kw (0.5 Hp)
Varnish pump	230V, 50 Hz, Single Phase AC
Impression ON / OFF	Pneumatically – operated
Dimension (LxWxH)	6750x2140x1680 mm (machine with dryer)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA