



Machine Introduction

DB-470 series automatic thermoforming machine, as the first domestic new-type machine, is researched and developed by our scientific researcher according to the market demands and our past production technology. This machine is a multi-station automatic machine, which solve the problems of food packaging hygienic standards. It not only solves a lot of problems effectively in the production of PP, PS, PET, PVC and PLA plastic products, such as large capital investment, large labor input, complicated production process, lower hygienic security, etc, but also has extensive usage. It can be used in the production of PP, PS, PET, PVC, PLA plastic products using in metals, food, pharmaceutical, etc. The machine enjoys beautiful appearance and good price. It is popular with the customers at home and abroad!

Applications:

PLA, PVC, PET, PS, PP as raw materials, changing the mold at one machine to manufacturing lids, covers, trays, plates, boxes, food and medical trays, etc.



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35 YEARS
SERVING
INDONESIA



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35 YEARS
SERVING
INDONESIA

Technical Specifications

Model	DB-470A
Suitable Products	Disposable Plastic lids, clamshell boxes, plates, (egg) trays, etc.
Suitable Material	PP, PS, PET, PVC, EPS and PLA
Max. Width of Material	510mm
Max. Forming Width	470mm
Max. Forming Length	260mm
Max. Forming Depth	50mm
Max. Cutting Speed	10-35 Cycles/min
Material Thickness	0.1mm-1.5mm
Power	380V/ 50HZ (Three-phase and four-wire)
Pressure of Water Supply	0.2MPa
Water Consumption	0.3m3/h (Tap water or Circulating cooling water)
Air Exhaust Volume	≥0.8m3/min
Air Pressure	0.6-0.8MPa
Machine Install Size	5000×1600×2000mm
Machine Packing Size	4700×1680×2100mm
Weight	3500KG

Features

		
Raw Material Feeding	Heating System	Forming System
		
Punching System	Cutting System	Servo Motor

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35 YEARS
SERVING
INDONESIA

		
Solenoid Valve	Frequency converter	PLC
		
Speed Reducer	Touch Screen	Low-voltage apparatus

Configuration

Name	Brand
Touch Screen	Siemens Germany
PLC	Siemens Germany
Encoder	OMRON Japan
Relay	Schneider France
Proximity switch	Schneider France
power switch	Schneider France
Servo Motor	INVT (Shenzhen, China)
Temperature module	Hexin China
Frequency converter	INVT (Shenzhen, China)
Circuit breaker	Schneider France
Button switch	Schneider France
Emergency stop switch	Schneider France
Solenoid valve	AIRTAC Taiwan
Cylinder	AIRTAC Taiwan
solid state relay	Yangming Taiwan
Reducer	Tongli China
pressure reducing valve	AIRTAC Taiwan

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35 YEARS
SERVING
INDONESIA