

GPL-5545DI+GPS-5030LW Automatic L Type Sealing and Shrinking Machine



Machine Introduction

This machine is the automatic equipment which can punch and bind in one machine, it can feed the book in different layer automatically, punching automatically, binding automatically, receiving the book automatically and so on. We have many patent in this machine, which can improve the working efficiency above 60%. The machine can be used for calendar, notebook, and notebook. It would be easy to operate the machine with the touch screen.

Technical Specifications

Model	GPL-5545DI	GPS-5030LW
Machine dimension	L1785×W1420×H1340mm	L2000×W1100×H1250mm
Packing size	L≥100mm W+H<380mm H<180mm, L+H<480mm	L1200×W450×H250mm
Cutter size/ tunnel size	L550×W450mm	L1500×W500×H300mm
Customer product size	/	/
Packing speed	25-35Pcs/min	30-40Pcs/min
Net Weight	550kg	650kg
Power	3KW	16KW
Power supply	220V/380V 50Hz/60Hz 3 Phase	220V/380V 50/ 60Hz, 3 Phase
Air pressure	5.5kg/cm ³	/
Table height	850+30mm	850+30mm
Max current	16.5A	30A
Direction	Right to left	Right to left
Material	POF	POF

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Configuration List

GPS-5030LW		GPL-5545DI	
Part Name	Brand / Origin	Part Name	Brand / Origin
Temperature Control	Japan Omron	PLC	SIEMENS
Motor	Taiwan motor	Touch panel	MCGS
Frequency Changer	Taiwan DELTA	Sensor	German SICK
Contactora	France Schneider	Intermediate Relay	Japan OMRON
Middle relay	Japan IDEC	Temperature Controller	OMRON
		AC Contactora	Schneider
		Pneumatic Parts	Taiwan Sharko
		Sensor	BANNER

Horizontal sealing blade



Vertical sealing blade



Waste film collection



POF material device



Electrical panel



Sample

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

