

# FL-6560TBD

## Shrink Packaging Machine



### Packaging Machinery

### Shrink Packaging Machines

#### 01 Description

Easy operation, excellent price and quality ratios are the main features characterizing on FL-5545TBD. It can indeed be supplied with or without shrink tunnel. Comparing with automatic L-bar sealer system, its most advantage is its height is up to 250mm max. This model is widely used in large quantity shrink wrapping industries, such as CD, DVD, cosmetics, printings, frame photos.



#### 02 Features

- 01 Sealing part adopt vertical drive. Sealing interface is even vertical drive can overcome the wrinkle from auto L sealer and sealing line is not in the middle of the product and can achieve the excellent effect
- 02 Adopts most advanced PLC, with safety protection and alarm device, ensure its continuous sealing action, with simple maintenance
- 03 Film in-feeding length controlled by electric eye and timer, accurate control makes letter shrinking
- 04 There are horizontal and vertical electric eyes, easy to switchover, and also easy to pack the thin and small products
- 05 Auto remaining film reeling controlled by one motor, the remaining film will not break even if film is too loose or too tight
- 06 To pack different sizes of product, sealing cutter's up and down controlled by a motor, the operator just need to press the button
- 07 Blowing system is optional according to the size of packagers
- 08 SM-5030LX adopts down blowing system, and wind force is controlled by a frequency inverter
- 09 Conveyor is controlled by a frequency inverter, and conveying speed is adjustable
- 10 The cover on the top of the tunnel is open-able, and easy for cleaning and maintenance
- 11 With a visible window, you can see the whole shrink processing
- 12 In-feed power conveyor belt and out-feed roller conveyor belt is optional

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
 Jl. Terusan Bandengan Utara No.16 / B 3-4  
 Jakarta, 14450, Indonesia  
 Tel. (021) 660 2665, 661 8255.  
 Fax. (021) 668 5874, 660 2657



**30 TAHUN**  
**MELAYANI INDONESIA**  
**Anniversary 1982-2012**

# FL-6560TBD

## Shrink Packaging Machine

### 03 Technical Specification

|                                           |                       |
|-------------------------------------------|-----------------------|
| <b>Model</b>                              | <b>FL-6560TBD</b>     |
| <b>Machine dimension LxWxH (mm)</b>       | 2015x1470x1300        |
| <b>Tunnel dimension LxWxH (mm)</b>        | /                     |
| <b>Max packing size L+H (mm) H&lt;180</b> | ≤ 600                 |
| <b>Max packing size W+H (mm) H&lt;180</b> | ≤ 550                 |
| <b>Max sealing size LxW (mm)</b>          | 650x540               |
| <b>Packing speed (pcs/min)</b>            | 20-35                 |
| <b>Conveyor speed (m/min)</b>             |                       |
| <b>Net weight (kg)</b>                    | 850                   |
| <b>Power (kw)</b>                         | 3.2                   |
| <b>Power supply</b>                       | 1PH 220V/110V 50/60Hz |
| <b>Air pressure (kg/cm<sup>2</sup>)</b>   | 6-8                   |
| <b>Applicable film</b>                    | POF                   |

### Shrink Tunnel

|                                           |                       |
|-------------------------------------------|-----------------------|
| <b>Model</b>                              | <b>SM-5030LX</b>      |
| <b>Machine dimension LxWxH (mm)</b>       | 1800x990x1300         |
| <b>Tunnel dimension LxWxH (mm)</b>        | 1500x500x300          |
| <b>Max packing size L+H (mm) H&lt;180</b> | 1300x400x250          |
| <b>Max packing size W+H (mm) H&lt;180</b> |                       |
| <b>Packing speed (pcs/min)</b>            | 0-20M                 |
| <b>Conveyor speed (m/min)</b>             |                       |
| <b>Net weight (kg)</b>                    | 650                   |
| <b>Power (kw)</b>                         | 16                    |
| <b>Power supply</b>                       | 3PH 380V/220V 50/60Hz |
| <b>Air pressure (kg/cm<sup>2</sup>)</b>   | /                     |
| <b>Applicable film</b>                    | POF                   |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
 Jl. Terusan Bandengan Utara No.16 / B 3-4  
 Jakarta, 14450, Indonesia  
 Tel. (021) 660 2665, 661 8255.  
 Fax. (021) 668 5874, 660 2657



**30 TAHUN**  
**MELAYANI INDONESIA**  
**Anniversary 1982-2012**

# FL-6560TBD

## Shrink Packaging Machine

### Finger Push Conveyor

|                                                 |                                         |
|-------------------------------------------------|-----------------------------------------|
| <b>Model</b>                                    | <b>Feed fingers conveyor</b>            |
| <b>Machine dimension LxWxH (mm)</b>             | 3000x550x850                            |
| <b>Adjustable width of the defending boards</b> | ± 50 mm                                 |
| <b>Weight</b>                                   | Changeable as per the real requirements |

### Feeder FL-5545TBK-1

|                                     |                     |
|-------------------------------------|---------------------|
| <b>Model</b>                        | <b>FL-5545TBK-1</b> |
| <b>Machine dimension LxWxH (mm)</b> | 584x607x478         |
| <b>Max feeder size LxWxH (mm)</b>   | 200x200x5           |
| <b>Min feeder size LxWxH (mm)</b>   | 10x10x0.2           |
| <b>Feeder speed (pcs/min)</b>       | 0-300               |
| <b>Net weight (kg)</b>              | 80                  |
| <b>Power (kw)</b>                   | 0.1                 |
| <b>Power supply</b>                 | 1PH 220V 50Hz       |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



**30 TAHUN**  
**MELAYANI INDONESIA**  
**Anniversary 1982-2012**