



Machine Introduction

It has the centralized oiling device and electromagnetic chuck; it uses imported key electrical appliances and bearings for the key parts; it is the model of maximal automation among other competition products. The stepper motor and PLC are adopted to automatically set the frequencies of rough and accurate grinding, to feed grinding wheel, to memorize, store as well as track dynamically. It is an ideal grinding equipment for industries such as printing, paper making, wood working, plastics and leather, and also for the small-size grinding center as well as middle-small sized printing and packaging industry.

Main function:

1. Grinding wheel head
2. Maximum grinding width: Taken 22° as final 180 mm
3. Fixed grinding head Stroke speed (It can be customized)
4. Grinding wheel automatic feed
5. Rack and pinion
6. Grinding head
7. Maximum grinding width: taken 22° as final 180 mm
8. Grinding wheel automatic feed
9. Rack and pinion
10. Cantilevered fuselage structure
11. Mechanical Knife sets
12. Worm drive tool holder
13. Table rotation angle: $0 \pm 90^\circ$

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Main Function Deployment:

1. Linear guide rail
2. Centralized oiling device
3. Programmable logic controller
4. Dust cover configuration
5. Imported electrical components (optional)
6. Scraper clamp (optional)

Technical Specifications

Model	DMSQ-ZK
Maximum grinding width	It can be customized
Table size	It can be customized
Table straightness error	0.02/1000mm
Grinding head automatic feeding	0.001-0.05 (mm)
Grinding wheel dimension	φ200*100*φ150(mm)
Grinding head reciprocating speed	6m/min
Mode of cooling	Internal cooling system
Axis/longitude beat error of grinding head	0.005/0.01
Grinding rotation speed	1420r/min
Grinding motor power	3KW
Movement electromotor power	0.55KW
Coolant motor power	0.25KW
Blade straightness	0.03mm/1000
Surface roughness of 3 mm from blade	0.8 (hard alloy steel blade)
Machine tool appearance size and weight	
Grinding Angle adjustment	0~±90 °



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

