



Machine Introduction

It equipped AC digital servo controlling technology and 10 inches colorful touching screen, the data resolution rate is 0.01mm, Full touch operating system for human computer interface, has self-diagnostic function of troubles and displays the operating pattern, 100 program units, over 10000 different cutting positions, it can memorize, store and dynamic follow-up. The max paper-pushing speed is 5-15m/min. It adopts Japanese hydraulic components, Japan and Korean electric components. Japan, Taiwan ball lead screw and linear double guide-rail, PLC control system for electric configuration, Its key parts adopt imported bearing of low maintenance. IR ray protective device is more convenient for cutting with optical knife-line alignment, button operated by two hands, single circulation cutting device.

Technical Specifications

Model / Specifications	92	115	130
Cutting width(cm)	92	115	130
Max. cutting height without assistance pressing plate(cm)	13	16.5	13
Max. cutting depth(cm)	93	115	130
Min cutting depth without assistance pressing plate(cm)	2.5	2.5	2.5
Extended length of working table(cm)	65	73	73
Height of working table(cm)	86	88-92	86-91
Machine width including side working table(cm)	233	266	266
Total length of working table(cm)	198	226	241
Cutting speed(r/min)	45	45	45
Max. Paper pressure(n)	35000	40000	40000
Power of main motor(kw)	3	4	4
Motor for paper feeding(kw)	0.75	0.75	0.75
Air pump(kw)	0.55	0.75	0.75
Machine weight(kg)	3000	4000	3900
Overall dimension(cm)	228x140x195	255x160x215	260x153x195

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Technical Specifications

Name	Brand Model	Origin
Display screen + computer	WEINVIEW 10 inches color touch screen	Taiwan
Motherboard chipset	ATMTEL	America
Controlling PLC	Panasonic PLC	Japan
Drive under the knife	Flat worm reducer	Sino-US joint venture
Motor driver	SE Servo motor control system	joint ventures
Feed lead screw	ABBA Ball screw	Taiwan
Guide-rail	ABBA High-precision linear guide	Taiwan
Worktable	Slot less chrome platform with air cushion	HT2500 Casting
Bearing	MSK Bearing	Japan
Sensor	ROKO	Taiwan
Switch	Shuangke	China
Air switch	Yaohua	China
Power switch	Shuangke	China
Locating switch	Schneider	France
Contacts	Schneider	France
Post Button	TAYEE	China
Seals	MERKEL	Japan
Hydraulic Components	YUKEN	Japan
Passage control system	Relief	Japan

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA