



Technical Specifications

Performance	Model	KLD-15D
	Max. load capacity	1500kg
	With load center at	600mm
	Weight	700kg
	Max. lifting height	1600/2500/3000mm
	Travel speed (without load)	4.5km/h
	Travel speed (with load)	3.5km/h
	Lifting speed (without load)	140mm/s
	Lifting speed (with load)	135mm/s
	Lowered speed (without load)	150mm/s
	Lowered speed (with load)	155mm/s
	Ascend slope ability (without load)	7%
	Ascend slope ability (with load)	3%

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

Dimensions	Overall length of frame (mast no reach)	1810mm
	Overall length (mast no reach)	850mm
	Mast lowered height	2120/1835/2085mm
	Max height (mast lifted with backrest)	2165/3010/3510mm
	Wheelbase	1460mm
	Fork length	1150mm
	Fork outside with	680mm
	Fork inside with	340mm
	Fork thickness	65mm
	Ground clearance	15mm
	Fork lowered height	90mm
	Minimum turning radius	1430mm
Tire	Front wheel	85x70mm
	Drive wheel	210x70mm
	Caster wheel	130x55mm
	Wheel material	Polyurethane
Electrical components	Drive motor type	DC series motor
	Rated output	0.75kw
	Hoist motor type	DC series motor
	Rated output	2.2kw
Battery	Voltage	24V
	Capacity	100AH

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA