



Machine Introduction

Grinding Machine DMSQ-ZB is a third-generation magnetic chuck type end face grinding machines with uniform suction, safe and convenient operation which adopts quality magnetic chuck head. It improves the work efficiency effectively. It is ideal for grinding equipment used the printing, paper, wood, plastic leather, toilet paper and other industries.

1. Main Function

1.1 Grinding wheel head

1. Grinding motor German East Y series three-phase asynchronous motor
2. Type Y90L-4P
3. Power 1.5KW
4. Rotation speed 1400r/min
5. Maximum grinding width taken 22° as final 180 mm

1.2 Fixed grinding head stroke speed

1. Grinding motor German East Y series three-phase asynchronous motor
2. Type YS7124-W
3. Power 0.55KW
4. Rotation speed 1400r/min

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



1.3 Manual feed wheel: Feeding by the dial

1.4 Rack and pinion

1. Guarantee constant instantaneous transmission ratio, high stability
2. High transmitted power and large speed scope
3. Compact structure, accurate and reliable transfer motion, which can realize larger transmission ratio
4. Long lifetime, low noise

1.5 Cantilevered fuselage structure: machine bed is made by MF cast iron, grinding head works in The unilateral space of rail

1.6 Mechanical Knife sets

1. Special electromagnetic sucker for Grinding Machine designed by Tianming
2. With balanced suction, the knife pieces are difficult to transform, and it takes a more straight way to sharpen a knife.
3. Easy operation,
4. With functions of time delay demagnetization and reliable GPS, it has high work efficiency and is easy to operate.

1.7 Worm drive tool holder: flexible and stable rotation, high transmission ratio, low noise. Line contact between two gear wheels, large carrying capacity. Self-locking, guarantee the safety.

1.8 Table rotation angle: $0 \sim \pm 90^\circ$

2. Main Function Deployment

2.1 Dovetail guide rail

1. The high-frequency quenching contributes to high strength, sound abrasive resistance, good stability and prolonged service life.
2. Automatic self-aligning contributes to the smooth moves of high precision and stability
3. High rigidity in all directions, absorbing loads from up-bottom and left-right direction.

2.2 Dust cover configuration

1. It is made of non-woven fabrics and by high frequency hot seal and compression molding
2. It is capable of effective dust proof, waterproof, oil proof, lowering noise and improvement of work environment
3. It features acid and base proof as well as corrosion resistance to prolong service life
4. It is free of deformation under impact and shock, featuring high ratio of extension and compression

2.3 Imported linear guide rail

1. It ensures smooth moves of high precision and stable stroke drive
2. High rigidity in all directions absorbs loads from up-bottom and left-right direction as well as prolongs the service life of the guide rail
3. It adopts the excellent alloy linear guide rail, capable of easy replacement and maintenance as well as low cost

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications

Model	DMSQ-ZB
Maximum grinding width	1700MM
Machine size	2500*1100*1600MM
Machine weight	1500KG
Table straightness error	0.02/1000mm
Grinding head manual feeding	0.001 - 0.05 (mm)
Grinding wheel dimension	φ200*100*φ150(mm)
Grinding head movement speed	6 m/min
Mode of Grinding head's cooling	Internal cooling system
Axis/longitude beat error of grinding head	0.005/0.01
Grinding rotation speed	1420r/min
Grinding motor power	1.5/2.2KW
Movement electromotor power	0.55KW
Coolant motor power	0.125KW
blade straightness	0.03mm/1000
Linear guide rail	25mm
Grinding Angle adjustment	0~±90°

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

