



Box Type	A Max	A Min	B Max	C Min	D Max	E Min	F Min
Bottom Box	850mm	300mm	750mm	150mm	50mm	125mm	40mm
Straight Line Box	A Max	A Min	B Max	B Min			
	900mm	300mm	750mm	300mm			

Machine Introduction

Features:

1. The machine is running steady with strengthened single.side driving system, and it is also easy for maintenance.
2. The motor is controlled by transducers (inverter) which are available for automatic timing. Its power saved and it helps to work stably.
3. A doubleface tooth rods adjusting system in the machine will help to move carriers and adjust the position when doing different box.
4. Paper is feed by several thick belts under the help of vibration motor. Feeding is continuous, exact and automatic with this system.
5. Grinders are provided in both sides of machine, to make gluing more stable and firm.
6. There are two sets of gluing system in this machine top glue system and side glue system. Space adjustment is through the tooth rods.
7. There is a PLC system controlled by human through touch screen in this machine. A remote diagnosis is there to help maintenance (remote controller system for options), and a photoelectric system to control speed in pressing unit (speed in pressing unit is corresponding automatically with the one in feeding unit). Functions are more complete when it is able to count by accumulated quantitative or partitioned.
8. Delivery unit is equipped with pressing sponge belts to ensure output in a perfect condition. A transverse paper collection table after the pressing unit helps to collect boxes quickly.
9. The machine is able to make 2-fold or 4-fold crash-lock bottom boxes. In the pre-folding part, the first fold and the third fold can be at 180° and 90°. The second fold and the fourth fold are molded at 180°.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

Technical Specifications

Model	ZH-1200BFT
Line speed	0-200m/min, continuous adjustment
Usage paper	280-700 g/ms, paperboard, E Flute
Box forming	Bottom lock, straight line box, double walls box
Fold method	1 st & 3 rd folds 90°, 2 nd & 4 th folds 180°
Paper feeding	Automatic feeding, grinding unit
Electric power	13.2kw
Dimension	12 x 1.6 x 1.6 m
Weight	4700kg

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA