

SJFM-1300

Double Mainframe Extrusion Film Laminating Machine



Packaging Machinery

Shrink Packaging Machines

01 Description

SJFM-1300 Dual head compound extruding film machine is advanced machinery, which is consulted to foreign advanced technology, adopting engine, electricity, gas unitization comb in its design. It mostly applies to flexible packaging region: instant noodle packaging, paper, aluminum foil, BOPP film, etc. This equipment has high degree of automation, nice exterior, lower energy consumption, and high efficiency.

02 Features

1. Feeding Equipment

Construction:

- Double work-station bearing feeding frame
- Bearing air expansion feeding shaft

Specifications:

- Effective width: 1250mm
- Feeding max diameter: $\Phi 1300\text{mm}$
- Core: $\Phi 76\text{mm} / 3''$
- Max weight air expansion shaft support: 2000kg
- Tension setting: 10-200kg
- Tension control precision: $\pm 0.2\text{kg}$
- Magnetic controller 2 PCS
- Automatic tension controller 1 SET
- Air-expansion feeding unit 3 SET

Characteristics:

- Tension controller: According to replace material, you can input diameter and thickness parameter of the change material, along with the rotated-loops changing; tension is decreased proportionally to achieve automatic tension control.

2. Corona Treatment Device

Electric spark power: 6KW corona treatment adopts dustproof, interference-proof structure, pneumatic switch cover equipment, which achieve the function of discharging ozone.

3. Extrusion and Compounding Equipment

Construction:

- Three-roller film laminating unit and the back-pressure roller help to have even force on the laminating rubber with and the material firmly laminated.
- Silica-Stripping gluing roller: the laminated products are easy to be stripped from the cooling roller
- Arc roller film flat unit: it can help the film to spread quickly.
- The adjusting-roller for laminator and feeder can effectively conquer the defects like uneven thickness film.
- Round shearing unit.
- High-pressure fan side-sucking unit is to suck the material quickly.
- The Laminating-discharging-stripping roll.
- The Laminating roll is actuated by a vector frequency motor.
- The Laminating roll and the rolling speed synchronize in auto tension.
- The Cylinder buffering float swing-roll tests the tension and the precise retainer feedbacks.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012

SJFM-1300

Double Mainframe Extrusion Film Laminating Machine

02 Features continued

Specifications:

- Laminating roll: $\Phi 510 \times 1300$ mm 1PC
- Silica gluing roll: $\Phi 260 \times 1300$ mm 1PC
- Back-pressure roll: $\Phi 220 \times 1300$ mm 1PC
- 7.5kw speed reducer motor 1 UNIT
- 7.5kw vector frequency controller 1 UNIT
- Rotation coupling: 6 UNITS

Characteristics:

- The Cooling roll employs a mirror surface that can remove bubbles during laminating, featuring in quick stripping and laminating smoothly.
- The Silica gluing roll and laminating cooling roll employ screw cooling unit, featuring in fast cooling and that the cast film is easy to be formed.
- Vector frequency converter motor drives independently, which can adjust the speed of the main motor. Not only satisfy the different thickness requirement of laminating products, also assure the thickness and degree of homogeneity are the same

4. Extrusion Machine Device

Construction:

- Trolley extrusion machine
- Hanger-type Die
- Automatic PE feeding equipment
- Auto hydraulic pump filter changing device
- Extrusion machine can move back and forth, up and down
- Screw and charging barrel linkage area are all heated with cast aluminum board
- High power and helical gear speed reducer
- Temperature is controlled by Digital temperature controller automatically.
- Stainless steel hopper
- NO.6 heating zone is to control temperature of screw and charging barrel independently. ix screw and charging barrel heating zones are controlled independently.
- NO.7 heating zone is to control the temperature of inner die head independently

Specification:

- The effective width of the Die is 1400mm, with a hanger-type runner unit, film width: max 1250mm; the film width can be adjusted in the construction scope.
- Diameter: $\Phi 105$
- Length to diameter ratio: 32:1
- 22kw AC motor 1 UNIT
- 1.5kw moving motor

Characteristics:

- The Die is processed after be electroplated, which can ensure the equal and flat result of laminated film.
- The larger length-diameter ratio screw rod can completely melt the resin, which ensures that is the materials are not easy to be rolled by side while winding.

5. Second Feeding Equipment

Construction:

- 360 degree feeding frame
- Air expansion feeding shaft

Specifications:

- Feeding max diameter: $\Phi 600$ mm
- Core: $\Phi 76$ mm / 3"

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012

SJFM-1300

Double Mainframe Extrusion Film Laminating Machine

02 Features continued

- Max weight air expansion shaft support: 2000kg
- Tension control precision: $\pm 0.2\text{kg}$
- Magnetic controller 2 PCS
- Automatic tension controller 1 SET
- Air-expansion feeding unit 2 SET

Characteristics:

- Tension controller: According to replace material, you can input diameter and thickness parameter of the change material, along with the rotated-loops changing; tension is decreased proportionally to achieve automatic tension control.

6. Extrusion and Compounding Equipment

Construction:

- Three-roller film laminating unit and the back-pressure roller help to have even force on the laminating rubber with and the material firmly laminated.
- Silica-Stripping gluing roller: the laminated products are easy to be stripped from the cooling roller
- Arc roller film flat unit: it can help the film to spread quickly.
- The adjusting-roller for laminator and feeder can effectively conquer the defects like uneven thickness film.
- Round shearing unit.
- High-pressure fan side-sucking unit is to suck the material quickly.
- The Laminating-discharging-stripping roll.
- The Laminating roll is actuated by a vector frequency motor.
- The Laminating roll and the rolling speed synchronize in auto tension.
- The Cylinder buffering float swing-roll tests the tension and the precise retainer feedbacks.

Specifications:

- Laminating roll: $\Phi 510 \times 1300\text{mm}$ 1PC
- Silica gluing roll: $\Phi 260 \times 1300\text{mm}$ 1PC
- Back-pressure roll: $\Phi 220 \times 1300\text{mm}$ 1PC
- 7.5kw speed reducer motor 1 UNIT
- 7.5kw vector frequency controller 1 UNIT
- Rotation coupling: 6 UNITS

Characteristics:

- The Cooling roll employs a mirror surface that can remove bubbles during laminating, featuring in quick stripping and laminating smoothly.
- The Silica gluing roll and laminating cooling roll employ screw cooling unit, featuring in fast cooling and that the cast film is easy to be formed.
- Vector frequency converter motor drives independently, which can adjust the speed of the main motor. Not only satisfy the different thickness requirement of laminating products, also assure the thickness and degree of homogeneity are the same

7. Extrusion Machine Device

Construction:

- Trolley extrusion machine
- Hanger-type Die
- Automatic PE feeding equipment
- Auto hydraulic pump filter changing device
- Extrusion machine can move back and forth, up and down
- Screw and charging barrel linkage area are all heated with cast aluminum board
- High power and helical gear speed reducer
- Temperature is controlled by Digital temperature controller automatically.
- Stainless steel hopper

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012

SJFM-1300

Double Mainframe Extrusion Film Laminating Machine

02 Features continued

- NO.6 heating zone is to control temperature of screw and charging barrel independently. ix screw and charging barrel heating zones are controlled independently.
- NO.7 heating zone is to control the temperature of inner die head independently

Specification:

- The effective width of the Die is 1400mm, with a hanger-type runner unit, film width: max 1250mm; the film width can be adjusted in the construction scope.
- Diameter: $\Phi 105$
- Length to diameter ratio: 32:1
- 22kw AC motor 1 UNIT
- 1.5kw moving motor

Characteristics:

- The Die is processed after be electroplated, which can ensure the equal and flat result of laminated film.
- The larger length-diameter ratio screw rod can completely melt the resin, which ensures that is the materials are not easy to be rolled by side while winding.

8. Rewinding Device

Construction:

- Surface rewinding device (double work station), roll change without stopping the machine.
- Surface roll drive
- Drive motor
- Frequency speed regulator
- Pneumatic clamp device for Winding shaft

Specification:

- Rewinding Diameter: $\Phi 1300\text{mm}$
- Core Specification: $\Phi 76\text{mm} / 3''$
- Surface roller, hard Cr plated roll with high precision $\Phi 508\text{mm}$
- 7.5kw motor 1 UNIT
- 7.5kw vector frequency converter 1 UNIT
- Rewinding shaft clamping air cylinder $\Phi 80\text{mm}$
- Air-swollen feeding shaft

9. Other Device

- Guide roll: totally employed balance Al guide roll: $\Phi 120-90 \times 1300\text{mm}$
- Pneumatic elements: imported ones
- Cylinders employ Taiwan AIRTAC
- Lower voltage electric components employ UC Certificate products
- circuit breaker, Schneider French
- AC contactor, Schneider French
- 24V auxiliary relay, Schneider French
- 220V/N auxiliary relay, Japan Omron
- Button with lamp, knob indicator, mushroom head button, ONPOW
- Switching power supply (Taiwan Meanwell)
- Solid-State Relay (Zhejiang Mager)
- Control box use Siemens brand
- Whole machine is touch-sensitive screen man-machine interface

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012

SJFM-1300

Double Mainframe Extrusion Film Laminating Machine

02 Features continued

10. Technical Information

- Lamination unit installed foundation plan (contract signed within 20 days).
- Equipment manual (including equipment operation, maintenance, repair, etc.). (Delivery available)
- Electrical circuit diagram. (Delivery available)
- The equipment inspection and certification. (Delivery available)
- Random tools, wearing accessories (delivery)

11. Auxiliary Equipment (Provided by Customer)

- Power: three phase 380v 50Hz three-phase five-line
- Air supply: 6-8kg/m²
- Water resources: 2-3 kg/m²

03 Technical Specification

Model	SJFM-1300
Film coating resin	LDPE, PP, EVA, EAA, etc
Paper thickness	35-425 gsm
Max speed	80-150 m/min
Max lamination width	1250 mm
Film coated thickness	0.01-0.11mm
Film coated thickness error	±6%
Tension setting scope	10-150kg/whole width, tension
Max. extrusion capacity	250 kg/h
Total Power	About 170kw
Basic material rolling core ID	Φ76mm / 3"
Weight	18000kg
Overall dimension	12800 x 8500 x 3250 mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012