



Machine Introduction

- The machine is running steady with strengthened single-side driving system, and it is also easy for maintenance.
- The motor is controlled by transducers (inverter) which are available for automatic timing. It is power saved, and it helps to work stably.
- An electric adjusting system in the machine makes it more conveniently when adjusting the space of carriers which usually based on the double-face tooth rods adjusting system.
- Paper is feed by several thick belts under the help of vibration motor. Feeding is continuous, exact and automatic with this system.
- Grinders are provided in both sides of machine, to make gluing more stable and firmer.
- There are two sets of gluing system in this machine top glue system and side glue system. Space adjustment is through the tooth rods.
- There is a PLC system controlled by human through touch screen in this machine. A remote diagnosis is there to help maintenance (remote controller system is included), and a photoelectric system to control speed in pressing unit (speed in pressing unit is corresponding automatically with the one in feeding unit). Functions are more complete when it is able to count by accumulated quantitative or partitioned.
- Delivery unit is equipped with pressing sponge belts to ensure out-put in a perfect condition. A transverse paper collection table after the pressing unit helps to collect boxes quickly.
- The machine is able to make 2-fold or 4-fold crash-lock bottom boxes. In the pre-folding part, the 1st fold at 180° and the 3rd fold at 90°. The 2nd fold and the 4th fold are molded at 180°.
- Belts in the main part of the machine are imported.
- Pre-folding in 135° design/plasma device/spray gluing system is optional. And the special design is available.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.






PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Technical Specifications

Line speed	0-200m/min, Continuous adjustment
Usage paper	300-800 g/ms, paperboard, E/B Flute
Box forming	Bottom-lock, straight line box, double walls box
Fold method	1 st fold 180° & 3 rd folds 90°, 2 nd & 4 th folds 180°
Paper feeding	Automatic feeding, grinding unit
Electric Power	17.2kw
Dimension	14.0*2.1*1.65m
Weight	6200kg

Box Type	Sample	A	A	B	B	C	C	D	D
		Max	Min	Max	Min	Max	Min	Max	Min
Crash-lock Bottom Box		1250-350mm		900-400mm		300mm		50mm	
Straight Line box		1380-300mm		900-300mm					
Double Walls Box		980mm		900mm		150mm		800mm	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA