



Machine Introduction

- The machine is running steady with strengthened single. Side driving system, also easy for maintenance.
- The motor is controlled by transducers (inverter) which are available for automatic timing. It is power saved, and it helps to work stably.
- An electric adjusting system in the machine makes it more conveniently when adjusting the space of carriers which usually based on the double face tooth rods adjusting system.
- Paper is feed by several thick belts under the help of vibration motor. Feeding is continuous, exact and automatic with this system.
- Grinders are provided in both sides of machine, to make gluing more stable and firmer.
- There are two sets of gluing system in this machine top glue and side glue system Space adjustment is through the tooth rods.
- Delivery unit is equipped with pressing sponge belts to ensure out-put in a perfect condition. A transverse paper collection table after the pressing unit helps to collect boxes quickly.
- The machine is able to make 2-fold or 4-fold crash-lock bottom boxes. In the pre-folding part, the first fold 180°, the third fold can be at 90°. The second fold and the fourth fold are molded at 180°.
- To make the unsymmetrical folding corrected, an option for separate governor which can control speed in each side solely is available.
- The spare parts are: Siemens Motor, Schneider Electric/PLC/Transducer, Japanese NITTA Belts, YHY/NSK Bearings, Continental Timing Belts. All these will make running quicker and more stable. Except the normal cardboard boxes, E/B flute is also able to be done.
- The pressing unit is in pneumatic design (air pressure system) to firm the glue.

* semua unit spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.






PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Technical Specifications

Line speed	0-280m/min, Continuous adjustment
Usage paper	280-800 g/ms, paperboard, E/B Flute
Box forming	Bottom-lock, straight line box, double walls box
Fold method	1 st fold 180° & 3 rd folds 90°, 2 nd & 4 th folds 180°
Paper feeding	Automatic feeding, grinding unit
Electric Power	13.2kw
Dimension	12.5*1.8*1.6m
Weight	5300kg

Box Type	Sample	A Max	A Min	B Max	B Min	C Max	C Min	D Max	D Min
Crash-lock Bottom Box		1050-300mm		850-250mm		150mm		50mm	
Straight Line box		1150-300mm		850-300mm					
Double Walls Box		880mm		880mm		120mm		700mm	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA