

AEM-1080T

Fully Automatic Die Cutting and Foil Stamping Machine

全自动平压平模切烫金机



Further Feature

性能优点



超耐磨聚氨酯送箔装置，传动平稳可靠。

Foil Device adopt high Wear-resisting Polyurethane, Stable and reliable running.



纵模烫金的双断箔检测系统，实时检测金箔。

Dual foil detection system to check foil on real-time



独立的废箔收卷装置，可配机内收箔装置。

Separate foil recycle device mixed recycle box to make operation fast and easily.



推动式放箔架，可轻松推出机外，安装箔卷轻便、快捷。

Foil Holder with movable design, can push out of machine for place the foil easily and fast.




简便的横向放箔装置，轻松、方便。

Adopt transverse foil placement device, easy and convenient.




静电消除装置，使得纸张流畅，准确到位。

Static elimination device to make paper smooth and accurate.




纵向放箔辊（三辊）合理布局、伺服驱动。

Longitudinal foil roll (3 rolls) with rational distribution and servo drive.



特殊材料和加工工艺处理的蜂窝板轻松解决烫金版的定位。

The Honeycomb board made by special material and special processing, helps locating the stamping board.



手动穿箔装置，大大缩短穿箔的时间。

Manual Foil Wearing device greatly shorten the installing time.



高性能伺服控制系统，性能稳定，抗干扰力强。

High performance servo control system with high stability and anti-interference performance.



4KW纵向卷箔伺服电机，金箔走动稳定可靠。

4KW Longitudinal foil turning servo motor, moving foil stable and reliable.



四吸四送精密飞达头，厚薄纸皆宜，输出精度高。

Four air intake and four air outlet in paper feeder and operate the thin and thick paper with high-precision.

Main specification

主要技术参数

	最大纸张尺寸 Max. Paper Size (mm)	最小纸张尺寸 Min. Paper Size (mm)	最大模切尺寸 Max. Cutting Size (mm)	版框内档尺寸 Die frame inner size (mm)	模切钢板尺寸 Cutting plate size (mm)	最大烫印尺寸 Max. Foil stamping Size (mm)	最小叼牙尺寸 Min gripper needle size (mm)	横切工作精度 Cutting Precision (mm)	烫印工作精度 Foil stamping precision(mm)	最大模切压力 Max cutting pressure (T)	最高模切速度 Max cutting speed (s/h)	最高烫印速度 Max. Foil stamping speed (S/H)	箔卷最大直径 Max. Foil roll diameter (mm)	纵向箔卷宽度 Vertical foil roll width (mm)	横向箔卷宽度 Horizontal foil roll width (mm)
AEM-1080T	1080 × 780	400 × 330	1075 × 770	1100 × 790	1080 × 780	1060 × 760	7	≤ ± 0.125	≤ ± 0.125	300	7000	6500	Φ 250mm	15-1060mm	15-760mm
	纵向放箔轴 Vertical foil roll shaft (pce)	横向放箔轴 Horizontal foil roll shaft (pce)	加热温区数量 Controllable tem-perature area (pce)	可调温度范围 Temperature range (℃)	输纸码堆高度 Pre-stacking height (mm)	收纸码堆高度 Collection stack height (mm)	纸张适应范围 Application	白板纸 White board (mm)	瓦楞纸 Corrugated paper (mm)	主电机功率 Main motor power (kw)	加热温区功率 Heating area Power (kw)	总功率 Total power (kw)	整机重量 Weight (T)	机器外形尺寸[长+(预堆纸)×宽(+脚踏台)×高](mm) Dimension [L(+pre-stacking) × W(+platform) × H]	
	3	2	12	50~199	1550	1500	/	0.1~2	<4	11	24	60	17	5600(+1650) × 2550(+1400) × 2600	