

# FL-5545TBJ

## Shrink Packaging Machine



### Packaging Machinery

### Shrink Packaging Machines

#### 01 Description

Suitable for large quantity shrink wrapping industries such as software, foodstuff, cosmetics, printing, pharmacy, flooring, ceramics, beverage and beer etc.



#### 02 Features

- 01 Advance side sealer continuous motion at cross seal, servo control series realize perfect shrink wrap with top efficiency, applicable for mass packaging like CD, photo frame, books, magazine, electronic product and so on
- 02 Servo motor action performs stable, reliable, continuous packaging process in high speed running, smooth transport without product move and stop
- 03 Equipped with self adapt feeding system adjust feed speed automatically according to speed of host machine
- 04 Whole system be standby status when feed by manual or miss feeding, switch on automatically till to continued product feeds
- 05 Color touch operator interface accomplish all working date easily, the panel with date memory for various product allows quick changeover by simply calling up the needed date from the database. Error of shows on screen with automatic inspect function make easier for operator to do emendation
- 06 Continuous cross seal without gap at sealing line, waste film is 50% of other traditional equipments to save customer cost a lot
- 07 Whole performance controlled by servo motors includes feeding, film releasing, sealing, shrinking and out feeding, make it to smooth running in high seed
- 08 Able to increase logo locate function for printed film
- 09 Equipped with suitable feeding system to connect customer production line for different products, realize fully automatic packaging to save labor cost
- 10 SM-5030LH adopts advance blowing from tunnel's bottom, full use of heat to arise energy efficiency. Frequency inverter controls blowing, adjustable blowing direction and blowing volume form bottom
- 11 Visible window shows shrink process in tunnel, the top of tunnel can be opened for easy clear and maintain
- 12 Optional belts feeding or fingers pushing conveyor for meets product to seal consistently
- 13 Make suitable protect guilds for different products to fulfill customer needs
- 14 Distance among slide rollers at conveyor can be adjusted for different products to speed up packaging

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



**30 TAHUN**  
**MELAYANI INDONESIA**  
**Anniversary 1982-2012**

# FL-5545TBJ

## Shrink Packaging Machine

### 03 Technical Specification

|                                         |                       |
|-----------------------------------------|-----------------------|
| <b>Model</b>                            | <b>FL-5545TBJ</b>     |
| <b>Machine dimension LxWxH (mm)</b>     | 2735x1480x1300        |
| <b>Tunnel dimension LxWxH (mm)</b>      | /                     |
| <b>Max packing size L (mm)</b>          | Unlimited             |
| <b>Max packing size W+H (mm)</b>        | ≤ 400                 |
| <b>Cross sealing L/H (mm)</b>           | 450/150               |
| <b>Packing speed (pcs/min)</b>          | 60-120                |
| <b>Conveyor speed (m/min)</b>           | 60-120                |
| <b>Net weight (kg)</b>                  | 1100                  |
| <b>Power (kw)</b>                       | 4                     |
| <b>Power supply</b>                     | 3PH 220V/380V 50/60Hz |
| <b>Air pressure (kg/cm<sup>2</sup>)</b> | 6-8                   |
| <b>Applicable film</b>                  | POF                   |

### Shrink Tunnel

|                                           |                       |
|-------------------------------------------|-----------------------|
| <b>Model</b>                              | <b>SM-5030LX</b>      |
| <b>Machine dimension LxWxH (mm)</b>       | 1800x990x1300         |
| <b>Tunnel dimension LxWxH (mm)</b>        | 1500x500x300          |
| <b>Max packing size L+H (mm) H&lt;180</b> | 1300x400x250          |
| <b>Max packing size W+H (mm) H&lt;180</b> |                       |
| <b>Packing speed (pcs/min)</b>            | 0-20M                 |
| <b>Conveyor speed (m/min)</b>             |                       |
| <b>Net weight (kg)</b>                    | 650                   |
| <b>Power (kw)</b>                         | 16                    |
| <b>Power supply</b>                       | 3PH 380V/220V 50/60Hz |
| <b>Air pressure (kg/cm<sup>2</sup>)</b>   | /                     |
| <b>Applicable film</b>                    | POF                   |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



**30 TAHUN**  
**MELAYANI INDONESIA**  
**Anniversary 1982-2012**

# FL-5545TBJ

## Shrink Packaging Machine

### 2M Finger Push Conveyor

| Model                              | 2M Feed fingers conveyor |
|------------------------------------|--------------------------|
| Machine dimension LxWxH (mm)       | 2000x550x1000            |
| Tunnel dimension LxWxH (mm)        | /                        |
| Max packing size L+H (mm) H<180    | 500x380x130              |
| Max packing size W+H (mm) H<180    |                          |
| Cross sealing L/H (mm)             | /                        |
| Packing speed (pcs/min)            | /                        |
| Conveyor speed (m/min)             |                          |
| Net weight (kg)                    | 220                      |
| Power (kw)                         | 0.06                     |
| Power supply                       | 1PH 110V/220V 50/60Hz    |
| Air pressure (kg/cm <sup>2</sup> ) | /                        |
| Applicable film                    | /                        |

### Feeder FL-5545TBK-1

| Model                        | FL-5545TBK-1  |
|------------------------------|---------------|
| Machine dimension LxWxH (mm) | 584x607x478   |
| Max feeder size LxWxH (mm)   | 200x200x5     |
| Min feeder size LxWxH (mm)   | 10x10x0.2     |
| Feeder speed (pcs/min)       | 0-300         |
| Net weight (kg)              | 80            |
| Power (kw)                   | 0.1           |
| Power supply                 | 1PH 220V 50Hz |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



30 TAHUN  
MELAYANI INDONESIA  
Anniversary 1982-2012