



Machine Introduction

Function description

Unwinding part

1. The unwinding adopts shaftless hydraulic automatic lifting, magnetic powder brake, automatic tension, and the bearing weight is 2.5 tons.
2. With the manual adjustment system, the unloading material tightness can be controlled. The adjustable range: $\pm 20\text{mm}$
3. Adopt thread screw to move the frame left and right by motor to make the auto error-correction.
4. Corridor type feeding materials easily for operation.
5. Magnetic powder: 20KG
6. Brake: 2 sets

Traction part

The 5.5 KW servo motor drives the mirror surface and pinch roll.

Wastepaper recycles device

Using motor to blow out the wastepaper. The net cage should be prepared by customer.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Rewinding part:(automatic loading and discharging, easily for operation)

1. Rewinding the cut material by upper and bottom double bearing.
2. Each rewinding shaft with 1 set of 7.5 KW servo motor to drive the air shaft. The tension decided by the roll diameter. PLC controls SMC electric automatically to make all the sheet same thickness when do the multiple slitting. Because of the press roller, all the reels end face is smooth. it has the choice of pneumatic press roller and self-weight press roller. The screw type rewinding way can control the degree of the tightness of the finished products. With the increasing of the rewinding diameter, the servo motor speed goes down to extend the life of the air shaft. The air shaft never broken except the human factor.
3. It can choose the whole shaft tension without friction and the servo motor in torque control mode in PLC.

Rewinding and discharging automatic up and down.

Technical Specifications	
Model	WZFQ-1400A
Material type	for large rolling materials, such as PET, BOPP, PE, paper sticker, paper, compound printing paper and so on.
Material thickness	30-350g (paper)
Max. Diameter	1600mm
Paper roll	3" 6#12#for choice
Max width	1400mm
Roller width	1450mm
Slitting width	50-1400mm
Rewinding paper roll	3"
Rewinding max. Diameter	1200mm
Error-correction	150mm
Precision	+/-0.15mm
Max. Speed	400m/min
Slitting speed	30-350m/min
Power	23 KW
Weight	5800KG
Dimension	Length: 3800, width 3000, height 1800mm
Slitting tolls	standard for 15 ets, according to customer's requirement
Upper cutter	Φ125*85*1.2mm
Bottom cutter	Φ100*20*16mm
Rewinding shaft	2 pcs of 3"air shaft
Equipment	With the Φ90 hard aluminum oxide guide roller

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Configurations

No	Name	Specification	Qty	Brand
1	45# steel frame	Thickness of wallboard 40mm	1set	Shanghai Baosteel
2	2" air adjust air shaft		2pcs	
3	Main traction roll(mirror)	φ200*1450mm	2pcs	Hard chromium plating with glazing. Dynamic balance 500m/min. Precision G1.6
4	Rubber press roller	φ150*1450mm	1pcs	Imported silica gel, the hardness reach to 70degree, Dynamic balance 500m/min. Precision G1.6
5	Hardness aluminum oxide guide roller	φ90*1850mm	1	Hardness oxidation treatment, Dynamic balance 500m/min. Precision G1.6
6	Rewinding servo motor	7.5KW	2sets	zhima
7	Traction servo motor	5.5KW	1set	zhima
8	Unwinding pneumatic brake	20KG	2sets	Wenzhou
9	Motor for blowing the slitter edge	1.1KW	1	Wenzhou
10	bearing		some	HRB
11	Pneumatic part		some	huanhua
12	Electric proportional valve		2pcs	SMC
13	Unwinding pneumatic brake	20KG	2sets	Wenzhou
14	PLC	SIMATLC S7-200SMART	1pcs	SIEMENS
15	10" touch screen	TPC1061Ti	1pcs	MCGS
16	Proximity switch		1pcs	OMRON from Japan
17	Low-voltage apparatus		some	Schneider 、zhengtai
18	Power supply	S100-24	1pcs	Taiwan meanwell

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA