



Machine Introduction

Daheng label inspection rewinding machine performs full-width inspection for rotary labels. Industrial high-speed color camera is equipped to scan the label, inspect the print quality and variable code, and alert when print defects and variable code defects are found. Inspection software can be customized to store anti-fake data and images. When defect is detected, inspection system will alert with light and sound, and support to configure appropriate method to deal with defect.

Features:

SUPPORTING 3 TYPES OF INSPECTION MODES FOR VARIABLE CODE

- **Sequence inspection:** Load data file, validate the code one by one in accordance with code sequence in data file Inspecting repetition, wrong code, absence, bad code.
- **Existence inspection:** Load data file, inspect whether the code on the label is in data file Inspecting repetition, wrong code, absence, bad code.
- **Readability inspection:** Do not load data file, only check if the code can be read. Inspecting repetition and bad code.

SUPPORT TO

- Inspect sequence code, inkjet code, and related code.
- Record and generate data files for each slitting rolls.
- Generate statistic report.
- Equip defect review machines.
- Equip label sticker, ink-jet marker as optional marking devices.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

ANTI-FAKE IMAGE STORAGE

Anti-fake label contains randomly aligned fibers to correspond with 2D code, which is irreproducible relation between fiber alignment and 2D code. Inspection system needs to capture the image of fibers, and decrypt 2D code, correlate the image with 2D code, and then upload to server. Customer uses mobile to scan the 2D code on the package and connect internet to acquire the corresponding fiber-featured image, so customer can compare the feature of fibers and verify the authenticity of products.



Technical Specifications

Model	DH-FJ330-4K	DH-FJ330-8K
Max. inspection width	330mm	
Mode	Color	
Imaging resolution	Horizontal/vertical: 0.08mm/pixel	Horizontal/vertical: 0.04mm/pixel
Max. inspection speed	200m/min	100m/min
JPG saving speed	≥ 45m/min	≥ 35m/min
Inspected print defects	Dirt, missing print, deviation, poor trash-cleaning, color variance, mis-registration, etc	
Min. defect size	High contrast: 0.03mm ² Low contrast: 0.1mm ²	High contrast: 0.01mm ² Low contrast: 0.05mm ²
Min. inspected registration	± 0.1mm	± 0.05mm
Color variance	$\Delta E \geq 3$	
Variable code type	Numeric character; barcode; 2D code; QR, DM, PDF417	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Inspected coding rule of variable code	Inspected coding rule: sequence code, ink-jet code, related code. Inspected code defect: wrong code, repetition, code missing and bad code.	
Min. size of recognizable code	Numeric character: 2mm*1.5mm Barcode: thinnest line $\geq 0.3\text{mm}$ 2D code: 8mm*8mm (min. width and height of cube $\geq 0.3\text{mm}$)	Numeric character: 1mm*0.8mm Barcode: thinnest line $\geq 0.2\text{mm}$ 2D code: 6mm*6mm (min. width and height of cube $\geq 0.2\text{mm}$)
Operation system	Windows 7 64bit	
Network	GigE	

Reeler parameters

Max. mechanical speed	200m/min
Max. feeding width	330mm
Running roller width	350mm
Max. unwinding diameter	700mm
Max. rewinding diameter	500mm
Coiling mode	Suitable for internal and external
Unwinding and rewinding core	76mm
Slitting accuracy	$\pm 0.25\text{mm}$
Working power supply	AC380/50Hz/Three phase four wire
Dimensions (LxWxH)	2800x1400x1500mm
Air pressure	100 p.s.i

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA