



Machine Introduction

Size: 2500x1200

Max die-cutting size: 2400mmx1100mm

Parameter:

1. Computerized phase adjustment
2. Pneumatic lift cylinder function
3. Automatic repair function
4. Infrared counter function
5. Automatic left right-side movement
6. positive and negative point jog function

Feeding Unit

1. Automatic paper feeding system
2. The lifting die-cutting stick is equipped with photoelectric automatic and manual switching functions

Material:

1. All the transmission shafts adopt gear transmission to improve the precision of the machine. The material is made of 45# fine grinding and nitriding treatment, which greatly improves the service life.
2. The gear adopts straight teeth, the thickness of the gear is 80mm, the machining process has a fine grinding of the common normal line,
3. All the transmission shafts and gears are connected by a keyless connection ring, so that the shaft and the gear have zero clearance, and the shaft and the gear can be kept at the same center to improve the printing precision.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



4. Eccentric shaft drive adopts cross frame to make machine zero wear 5. Youli Rubber Pad uses Guangdong Ruijian Trading Company to import Italian Desley.
5. The wall is made of cast iron with a thickness of 60mm (solid), and the upper and lower die-cutting bars are 35mm thick (3mm down). The whole axis is statically balanced to make the machine run smoothly at high speed.

Technical Specifications

Model	CND-B2800
Maximum paper size	2500x1400mm
Maximum die cutting size	2400x1400mm
Minimum paper feed width	360mm
Main motor	5.5kw
Repair motor	0.75kw
Phase motor	0.18kw
Equipment host dimensions	5x1.5x2 m
Paper feeding production platform	3.75x3.8 m
Electrical appliances	
Name	Origin
Relay	Zhejiang Chint
Proximity switch	Shanghai Xinhua
Phase meter	Hebei Hongyang
Frequency converter	Shenzhen INVT
Contacteur	French Schneider
Button	French Schneider

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

