

SDSG-800R

Single UV Automatic Coating Machine



Machine Introduction

Features

1. The machine adopts inverter control and has reasonable structure and easy to operate.
2. Reasonable internal structure can effectively prevent the leakage of ultraviolet light.
3. The internal electric heat oven can be used alone Designed 20%,40%,60%,100%, and automatic constant temperature.

Technical Specifications

Model	SDSG-800R
Max. paper size	1020x720mm
Min. paper size	280x330mm
Max. coating width	720mm
Paper thickness	80-157g/m ² with air knife 157-600g/m ²
Max. feeding speed	75m/min
Total power	9.5kw
Weight	2200kg
Size	8520x1280x1950mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

SDSG-800R

Single UV Automatic Coating Machine

Main Electrical Configurations

Part Name	Brand
Main motor	Shanghai span
Coating roller (electroplating roller)	China
Sending and suction fan	Pioneer
Thermostats, relays, photoelectric switches	Schneider
Control button	Schneider
Contactor	Schneider
Air control original	Latitude and longitude
Bearing	Imported bearings and some Harbin bearings
Paper feed mechanism	Zhuji

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA