



Machine Introduction

- The machine is running steady with strengthened single side driving system, and it is also easy for maintenance.
- The motor is controlled by transducer (inverter) which is available for automatic timing. It is power saved, and it helps to work stably.
- Paper is feed by several thick belts under the help of vibration motor. Feeding is continuous, exact and automatic with this system.
- Grinders are provided in both sides of machine, to make gluing more stable and firmer.
- The machine is able to fold and glue straight line boxes.
- In the pre-folding part, the first fold and the third fold can be at 180° and 135°. The second fold and the fourth fold are molded at 180°. Options for 180°.
- There is a PLC system controlled by human through touch screen in this machine to make operation more convenient.
- This model is upgraded to be a high-speed model with a reinforced body.
- The main equipment's are: Siemens Motor, Schneider Electric/Transducer, Japanese Nitta Belt, Japanese Bearing etc.
- The machine speeds up to 300m/min.

Technical Specifications

Line speed	0-300m/min, Continuous adjustment
Usage paper	220-600 g/ms, paperboard
Box forming	Straight line box
Fold method	1 st fold 180° & 3 rd folds 135°, 2nd & 4th folds 180°
Paper feeding	Automatic feeding, grinding unit
Electric Power	8.0kw
Dimension	9.6*1.2*1.3m
Weight	2800kg
Voltage	380V50HZ


* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Box

Box Type	Picture	A Max	A Min	B Max	B Min
Straight Line Box		580-110mm		600-60mm	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA