



Machine Introduction

It equipped AC digital servo controlling technology and 10 inches colorful touching screen, the data resolution rate is 0.01mm, Full touch operating system for human computer interface, has self-diagnostic function of troubles and displays the operating pattern, 100 program units, over 10000 different cutting positions, it can memorize, store and dynamic follow-up. The max paper-pushing speed is 5-15m/min. It adopts Japanese hydraulic components, Japan and Korean electric components. Japan, Taiwan ball lead screw and linear double guide-rail, PLC control system for electric configuration, its key parts adopt imported bearing of low maintenance. IR ray protective device is more convenient for cutting with optical knife-line alignment, button operated by two hands, single circulation cutting device etc.

Technical Specifications

Model / Specifications	92
Cutting width(cm)	92
Max. cutting height without assistance pressing plate(cm)	13
Max. cutting depth(cm)	93
Min cutting depth without assistance pressing plate(cm)	2.5
Extended length of working table(cm)	65
Height of working table(cm)	86
Machine width including side working table(cm)	233
Total length of working table(cm)	198
Cutting speed(r/min)	45
Max. Paper pressure(n)	35000
Power of main motor(kw)	3
Motor for paper feeding(kw)	0.75
Air pump(kw)	0.55
Machine weight(kg)	3000
Overall dimension(cm)	228x140x195

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA