



Machine Introduction

The machine has a board punch cover and inside pages automatic models, to meet customer needs different binding. The mold is made of high quality steel is refined, and a variety of specifications for selection, suitable for various drilling requirements (please refer to "punch die chart").

Features

1. Punching speed up to 90 rpm.
2. Maximum punching width 590mm (with the conveyor option).
3. Two discharge options- a high pile reception unit or a conveyor-are available.
4. Can handle different paper thickness from 60gsm to 500gsm.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

Technical Specifications

Model	JTM-24
Max. paper size (W x L)	530x500 mm
With high pile reception unit with conveyor	600x500 mm
Max. paper size (W x L)	140x220 mm
With high pile reception unit with conveyor	140x100 mm
Max. punching width	520 mm
With high pile reception unit with conveyor	590 mm
Max. paper thickness	2 mm
Paper specification	60 ~ 500 g/m ²
Max. pile height	880 mm
Max. cycle speed	8,280 cycles/hr
Normal working speed	5,400 cycles/hr
Min. working speed	1,500 cycles/hr
Stroke	13 mm
Power supply	380V / 3 ph / 50Hz
Power consumption	3 kW
Dimension (L x W x H)	2800 x 1280 x 1400 mm
With high pile reception unit with conveyor	2800 x 1470 x 1400 mm
Net weight	1400 kg
Air compressor (not included)	0.37 kW
Air pressure	4 ~ 6 bar
Accessories	One set of punching tool: round hole, pitch: 6mm or square hole, 4mmx4mm, pitch: 3:1"

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA