



Machine Introduction

Suitable for automatic stripping of tags/cards, color boxes, transparent plastic boxes, gray boards, special paper and other products.

Performance and quality:

- Longmen's institutional design is more stable than "bird's mouth" The machine main board is made of national standard steel plate, which can ensure the installation accuracy of linear guide, ball screw, servo motor and other components. Thus, the stability and service life of the equipment used at high frequency are guaranteed, and the maintenance cost is minimized.
- The whole machine adopts the high-quality standard parts and electrical components from the world's first-class suppliers to ensure the stability, reliability and operation safety in production. Main electrical appliances: Taiwan Delta, France Schneider, Japan OMRON. Key components: Taiwan Hiwin and Taiwan AirTac.
- The worktable is polished with stainless steel panel, which ensures smooth movement of paper and does not cause scraping. Compared with the electroplating treatment of similar products on the market, there is no need to consider the problem of surface damage and rust.
- HM and PLC computer control, full-color touch screen, so that operators can easily and accurately complete the debugging of the machine and order replacement. The order memory function can store and memorize 160 products.
- Equipped with grating protection to ensure safety in production.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

HR-1050QFC

High-speed Stripping Machine

Technical Specifications

Model	HR-1050QF	HR-1050QFC
Hydraulic power	The maximum output power is 300kg, and the output power range is 100kg to 300kg	
Drive	Servo subdivision motor is used to transmit, motion through precision screw ball	
Measuring device	Multi direction servo technology, photoelectric device measurement accuracy, sealing design can prevent dirt	
Weight	2T	2.33T
Dimension	2800x1850x1800mm	3500x1850x1800mm
Max. paper size	1080x735mm	
Min. paper size	300x300mm	
Max. stripping size	425x425mm	
Min. stripping size	50x50mm	
Pilling height	50-120mm	
Stripping speed	1-22mm	
Max. working pressure	3.8T	
Pressure	8	

Technical Specifications

Product name	Specification	Brand
Servo motor	MS-80ST-M02430B-20PT	Delta(Taiwan)
Servo drive	DS2-20PT-BSW	Delta(Taiwan)
PLC	HCA2-24X16YT	Delta(Taiwan)
Touch screen	TX7062KB	WEINVIEW(Taiwan)
Hydraulic system	VP-20	Hua Kai (Taiwan)
Linear guide rail		Hiwin (Taiwan)
Ball screw		Hiwin (Taiwan)
Switching Power Supply	NES-100-24(100W)	MEANWELL (TAIWAN)
Proximity switch		FOTEK (Taiwan)
Keys switch		Schneider (France)
Relay		Schneider (France)
Guide rod	Straightening chrome rod	XINFEI
Cylinder		AirTac (Taiwan)
Hydraulic system		Xing Ya (Taiwan)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA