



Machine Introduction

It equipped AC digital servo controlling technology and 10 inches colourful touching screen, the data resolution rate is 0.01mm, Full touch operating system for human computer interface, has self-diagnostic function of troubles and displays the operating pattern, 500 program units, over 340000 different cutting positions, it can memorize, store and dynamic follow-up. The max paper-pushing speed is 5-16m/min. It adopts Japanese hydraulic components, Japan and Korean electric components. joint venture ball lead screw and linear double guiderail, its key parts adopt imported bearing of low maintenance. IR ray protective device is more convenient for cutting with optical knife-line alignment, button operated by two hands, single circulation cutting device etc.

Technical Specifications

Model	115P
Cutting width (cm)	115
Max.cutting height without assistance pressing plate (magnetic rubber/plate) (cm)	16.5
Max.cutting depth (cm)	115
Min cutting depth without assistance pressing plate (magnetic rubber/plate) (cm)	2.5
Extended length of working table(cm)	73
Height of working table(cm)	88-92
Machine width including side working able (cm)	266
Total length of working table (cm)	226

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657



Cutting speed (r/min)	45
Max. Paper pressure (n)	40000
Power of main motor (kw)	4
Motor for paper feeding (kw)	0.75
Air pump (kw)	0.75
Machine weight (kg)	3800
Overall dimension (cm)	252x143x198/3130x1120x2150

Main Technical Parameters

No	Name	Brand Model	Brand Place
1	Display screen+computer	Qunchuan 10 inches color touch screen	Taiwan
2	Motherboard chipset		Joint ventures
3	Worm reducer		China
4	Motor driver	Servo motor control system	Joint ventures
5	Feed leadscrew	Ball screw	Joint ventures
6	Guide-rail	High-precision linear guide	Joint ventures
7	Worktable	Slotless chrome platform with air cushion	HT250 Casting
8	Bearing	MSK Bearing	Japan
9	Sensor	OMRON	Japan
10	Switch	MACK	Taiwan
11	Air switch	LS	Korean
12	Power switch	SANLI	Taiwan
13	Locating switch	Schneider	France
14	Contacts	Schneider	France
15	Host Button	SHANGHAI	Joint ventures
16	Bridge rectifier	SEP	Taiwan
17	Seals	MERKEL	Japan
18	Hydraulic Components	YUKEN	Japan
19	Hydraulic Fittings	HONDA	Japan
20	Passage control system	ZHEJIANG	joint ventures

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

