

ZD-QFJ18

Fully Automatic Roll Feeding Square Bottom Paper Bag Making Machine



Packaging Machinery

Paper Bag Making Machines

01 Description

This machine is designed for the production of square bottom paper bags with handles from paper reel in blank or printed. Since all steps are completed in an online way, this machine is an ideal equipment for making square bottom paper bags with handles. The whole machine is centrally controlled by computer system with touch screen and servo motor for cut-off length control, so it can produce paper bags of variable sizes.

02 Features

- 01 Touch screen is adopted for input control and machine status display, so as to finish machine correction easily.
- 02 Equipped with originally imported SIEMENS electrical system and servo motor drive, to make the machine run steadily.
- 03 Germany SICK photoelectric detector is used to track the material to be printed, reduce the adjusting time and improve production efficiency.
- 04 Separate single-station unwinding rollstand with hydraulic lifting device; Convex-type inflatable shaft for loading material (or shaftless loading); Magnetic powder brake for unwinding and automatically constant tension controller for unwinding tension control; EPC web guide control system for material alignment; alarm function for reminding replacing material and stopping-machine device for detecting material broken.
- 05 The handle making component is an independent machine, which is driven by servo motor and synchronized with the main motor; handle length is adjustable according to bag size.
- 06 Adjustable forming mould structure (side sealing is above the forming mould); automatic glue-spraying device with automatic disengaging function is used for side gluing.
- 07 Paper bags are delivered by belt, and collected at side workbench, which is easy for operations; automatic counting function.

03 Technical Specification

Model	ZD-QFJ18
Paper size range	660-1290 mm
Tube length	380-640 mm
Bag body width	240-450 mm
Paper thickness	90-180 gsm
Max. production speed	120 bags/min
Power	43 kw
Total Weight	Approx 16000 kg
Overall Dimensions	14500x6000 x2500 mm

