



Machine Introduction

Features:

1. The oven adopts internal hot air circulation type, and the temperature indicating regulator can control and stabilize the temperature in the drying tunnel at any point within the range of normal temperature $\sim 200^{\circ}\text{C}$. Ensure that the temperature difference in different areas inside the oven is within $\pm 10^{\circ}\text{C}$.
2. the temperature required for the product can be baked according to customer requirements. It can also be preheated and sealed.
3. the oven uses digital display temperature control regulator and sensor; temperature digital display PID automatic calculation, automatic control, we only need to set the target temperature, rise to the required temperature to achieve automatic alarm and stop heating. Temperature fluctuation: $\leq \pm 2^{\circ}\text{C}$, temperature error should be $\leq \pm 3^{\circ}\text{C}$.
4. With digital display time control device, the working time can be set arbitrarily within the range of 0.01-99.99 hours. The constant temperature delay automatically cuts off the heating and gives an alarm.
5. control cabinet: with power switch, air protection switch, AC contactor (Chint). With over-temperature and power-off protection, leakage protection. Both the vulcanization oven and the prepolymer preheating oven adopt a hot air circulation type to ensure the sensitivity of the heating system and the hot air circulation system control.
6. It adopts intelligent program temperature controller to control temperature, PID parameter self-tuning, solid state relay power adjustment, continuous contactless adjustment, automatic completion of drying process, can meet the requirements of any curing curve, easy to operate,

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

reliable performance.

7. It is equipped with a thermal element probe to form an automatic constant temperature control. Temperature control accuracy is sensitive, and the temperature can be arbitrarily selected at room temperature ~200 °C. The temperature inside the studio can be read directly from the meter.
8. The temperature control system of this machine has functions such as temperature control, timing and over temperature alarm.
9. Reasonable air duct and circulation system make the temperature uniformity change in the working room small. The motor and the fan blade have air convection breeze device, and the inner cavity air can be renewed and circulated.
10. All electrical switching components adopt brand, have power-off protection function, have leakage protection function and overload protection function, and all other instruments and equipment's are not affected by electromagnetic interference when the equipment is operated under various working conditions.
11. The oven control system is equipped with an anti-overheating device to ensure that the device issues an alarm and stops heating when the temperature control table is damaged.

Technical Specifications

Model	XGDRY-A
Working temperature	normal temperature - 200 ° C
Temperature controller fluctuation value	±5 °C, temperature uniformity: ±10 °C
Constant temperature timing	0.01--99.99 hours (time to cut off heating, buzzer prompt)
The size of the oven	1400 * 1000 * 1800mm (width X deep X high)
Voltage	380V 50H
Power	15 KW
Machine Dimensions	1600*1600*1400mm
Internal dimensions	1200*1200*1000mm

Customer experience: The temperature of the 100 °C paper pipette will be dried in 60 minutes.



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA