

BTH-450 + BM-500L

Side Sealing & High Speed Automatic Shrink Packaging Machine



Packaging Machinery

Shrink Packaging Machines

01 Description

Suitable for large quantity shrink wrapping industries such as software, foodstuff, cosmetics, printing, pharmacy, flooring, ceramics, beverage and beer etc.

02 Features

- 01 The machine adopts imported touching screen, on which all settings and operation can be done. Meanwhile, various product data can be stored in advance, and operator only to select parameters from the computer while usage.
- 02 According to different collocations for the machine and different products, the max packing speed is up to 80pcs/min.
- 03 Constant temperature heat sealing and cutting system is suitable for PE, POF etc, industrial standard shrink films, the seal is firm and nice, especially applicable for POF film, adjust the conveyor with the head wheel for packing products of different size. The reliability is higher and easier to operate it.
- 04 The front feed in systems speed is adjustable, combines a worktable at the end of the tunnel, makes whole machine highly automatic, it runs automatically without an operator comes true.
- 05 BM-500L Hi-speed hot air circulating shrink tunnel adopts roller type conveyor, the rollers are covered by silicone gel pipe, they roll automatically, also the conveyor can use Teflon mesh belt or S.S. mesh belt instead of rollers. When shrink PE film, need not the rollers roll, easy to convert it by the handle at the end of the tunnel.
- 06 The temperature inside the tunnel is even, suitable for shrink PE,PVC,POF films.
- 07 The inner container forms hot air circulation inside tunnel, the volume of hot air can be controlled by the air doors according to the packing requirements for different products.

03 Technical Specification

Model	BTH-450	BM-500L
Max Packing Size	(L) (W+H)≤400mm (H)≤130mm	(L)1500×(W)450×(H)250mm
Max sealing Size	(W+H)≤450mm	(L)1500×(W)500×(H)300mm
Packing Speed	30~80 packs/min	30~80 packs/min
Electric Supply & Power	380V/50Hz 3kw	380V/50Hz 16kw
Max Current	10 A	32A
Air Pressure	5.5kg/cm ³	/
Weight	800kg	650kg
Overall Dimensions	(L)2050×(W)1500×(H)1300mm	(L)1800×(W)1100×(H)1300mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



30 TAHUN
MELAYANI INDONESIA
Anniversary 1982-2012