



Machine Introduction

7 inch full touch LCD, the resolution rate is 0.05mm, has self-diagnostic function of troubles and displays the operating pattern, 60 program units, over than 6000 different cutting position, dynamic follow-up. The max paper-pushing is 5-10m/min. Adopted import hydraulic components, France, Japan, Korea electric components, Taiwan ball lead screw, adopted imported bearing of low maintenance. Linear double guide-rail and slot less working table to ensure the accuracy of cutting. Flat worm speed reducer transmission for cutting, IR ray protective device is more convenient for cutting with optical knife-line alignment, button operated by two hands, single circulation cutting device etc.

Technical Specifications

Cutting width (cm)	130
Max. cutting height without assistance pressing plate (cm)	13
Max. cutting depth (cm)	130
Min cutting depth without assistance pressing plate (cm)	3
Extended length of working table (cm)	73
Height of working table (cm)	86
Machine width including side working table (cm)	266
Total length of working table (cm)	241
Cutting speed (r/min)	45
Max. Paper pressure (n)	40000
Power of main motor (kw)	4
Motor for paper feeding (kw)	0.75
Air pump (kw)	0.75
Machine weight (kg)	3900
Overall dimension (cm)	260x153x195

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA