



Machine Introduction

Features:

1. Paper loading plate of feeder can land to ground to load paper pile easily
2. Suction device guarantees stability and smooth of paper sending
3. Bigger heating roller with electromagnetism technology ensures high quality lamination
4. Separation structure design makes operation and maintenance easily
5. New design of double layer patting plate of auto stacker makes operation easily



Auto Feeder

Servo controlled feeder and a photoelectric sensor to ensure that paper is continuously fed into the machine



Anti-curvature Device

The machine is equipped with anti-curl device, which ensures that paper remains flat and smooth during the lamination process



Automatic Stacker

Automatic stacker collects laminated paper sheet high efficiently and pat paper in good order as well as counter



Electromagnetic Heater

Equipped with advanced electromagnetic heater. Fast pre-heating. Energy saving. Environmental protection.



Suction Device

Suction device guarantees stability and smooth of paper sending



Hot stamping rewinder for pre-printing (optional)

It applies for rewinding waste film of paper hot stamping with separation design. It's optional.

Technical Specifications

Model	SW-760
Max. paper size	760x820mm
Min. paper size	210x300mm
Paper thickness	90-600g/m ²
Laminating speed	0-60m/min
Voltage	380V
Laminating temperature	80-110°C
Gross power	20/12kw
Total weight	3000kg
Overall dimensions	4600x1550x1700mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657

