



Machine Introduction

DXS Series Automatic Computerized High Speed Vacuum Forming Machine (Thermoforming Machine). It is designed by the principle of mechanical-electrical-pneumatic integration. Adopts PLC control system, panel and AC voltage meter adjustment. It is full-automatic forming equipment for thermoforming plastic sheet includes feeding, heating; forming, cooling, mold ejecting, cutting at one blow. These machines have luxury configuration and gets reliable performance and handy operation.

Features:

1. It is suitable for thermoforming PS, HIPS, PVC, PET, PP, flocking sheet that can produce varieties of blister package and blister tray. For example: egg tray, curatorial injection tray, oral liquid tray, mobile telephone tray, cookies tray, egg tray, one-off tableware etc.
2. Industrial computer control system and temperature module, it can set & display temperature on panel directly, more precision and easy operation.
3. DXS-700/1200B is not only has the function of DXS-700/1200-A, but also is the best forming equipment for thermoforming the latest degradable material (the degradable material of starch).
4. DXS-700/1200C Automatic Computerized High-Speed Vacuum Forming Machines (Thermoforming Machine) are our third generation products. Comparing with DXS-700/1200A machine, it is more professional design, more perfect construction & better configuration.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

Technical Specifications

Model	DXS-700/1200A-1	DXS-700/1200A-2	DXS-560/900
Length of forming	760-1200mm	760-1200mm	450-900mm
Width of forming	500-700mm	500-700mm	300-560mm
Height of forming	≤ 165mm	≤ 165mm	≤ 100mm
Production speed	60-720 Cycles/hr	60-720 Cycles/hr	60-720 Cycles/hr
Power of oven	24KW	24KW (Upper Oven), 18KW (Lower Oven)	16KW
Power of vacuum pump motor	3KW	3KW	1.5KW
Vacuum pump capacity	100 m³/h	100 m³/h	63 m³/h
Power of air compressor	15 Kw	15 Kw	11 Kw
Air displacement of air compressor	1.5 m³/min	1.5 m³/min	1 m³/min
Voltage	380/420V 50HZ	380/220V 50HZ	380/220V 50HZ
Overall dimensions	7950x1450x2550 mm	7950x1450x2550 mm	6600x1250x2150 mm
Weight	3000 Kg	3500 Kg	2000 Kg

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA