



Function Description

Features:

1. Equipment appearance professional industrial design, spray-paint process, practical and beautiful.
2. Non stop feeder, vertical dual functions laminator, automatic slitting (round knife suitable for OPP, BOPP), automatic collector.
3. The cutting device can be selected with chain knife and hot knife system, meet the needs of all kinds of film cutting.
4. The cutting device with a tension controller, bouncing function, ensure paper flat and unwinding.
5. High quality pneumatic conveying paper feeder with 4 suckers for lifting paper and 4 suckers for conveying paper to ensure stable and fast paper feeding.
6. Overlap device is controlled by side pull gauge and servo motor, ensure accuracy.
7. Paper conveying plate with customize corrugated stainless-steel plate.
8. The hot press roller adopts electromagnetic heating system, uniform temperature, high efficiency and energy saving, it will ensure high quality products film laminating requirements.
9. The electrical configuration mainly adopts the Taiwan Delta electrical control system and the French Schneider electric appliance.
10. Auxiliary cart lifting changing roll film, single person independent operation.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Technical Specifications

Model	FM-800H	FM-1080H	FM-1280H
Max. paper size	780x880mm	1080x1100mm	1280x1250mm
Min. paper size	350x270mm	360x290mm	360x290mm
Speed	10-90m/min	10-90m/min	10-90m/min
Paper thickness	80-500g/m ²	80-500g/m ²	80-500g/m ²
Overlap precision	≤±2mm	≤±2mm	≤±2mm
Film thickness (common micrometer)	10/12/15	10/12/15	10/12/15
Common glue thickness	4-10g/m ²	4-10g/m ²	4-10g/m ²
Pre-gluing film thickness	1005,1006,1206 (1508 and 1208 for deep embossing paper)		
Non stop feeding height	1150mm	1150mm	1150mm
Collector paper height (incl. pallet)	1050mm	1050mm	1050mm
Main motor power	5kw	5kw	5kw
Whole machine power	65kw	65kw	65kw
Working power	35-45kw	35-45kw	35-45kw
Voltage	380V-50Hz-3P	380V-50Hz-3P	380V-50Hz-3P
Roll working pressure	15Mpa	15Mpa	15Mpa
Air pressure requirement	1.0 Bar	1.0 Bar	1.0 Bar
Air consumption	80m ³ /h	80m ³ /h	80m ³ /h
Cable thickness	25mm ²	25mm ²	25mm ²
Dimension (LxWxH)	7400x1900x2700mm	8400x2200x2700mm	8800x2400x2700mm
Net. weight	7500kgs	9200kgs	9500kgs

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA