



Machine Introduction

The machine is designed for aiming at the hard distortion printing stock, the printing scope is very widely and can be used for screen printing of many plane bodies, such as paper, plastic, glass, ceramics, metal, textile and leather etc, especially for the printing of electron field PCB, soft PCB, PCB liquid state sensitization glue, SMT tin cream.

Features:

1. The printing head goes up and down vertically along the back main part, operated expediently and occupies little acreage. The worm reducer motor with frequency conversion driven which can ensure it goes up and down quickly and stably; High precision preload linear lead rail is used with "ITALY MEGADYNE" in-phase belt, frequency conversion timing drive the speed reducer motor, which make the whole machine more stably and credibility and can get more higher movement precision.
2. The printing table is fixed in the machine frame by support table, the distance between screen frame and table is achieved by adjusting the height of main printing arm the stable degree is better than other model. The table surface is made of stainless steel and it's hard to scratch and distort, and plane degree of work table is less than 0.20mm, which ensure the printing pattern much more equal and clearer.
3. The inching and lock device of the table is separately which eliminate the error caused by lock table.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

JB-750II/960II/1280II Horizontal-lift Half-tone Printing Machine

JINBAO 劲豹

4. Two cylinders control the movement of squeegee and ink reclaim blade separately, the pressure is large and equal and can be step less-regulated separately which increase the service life of half-tone and printing quality.
5. The printing course control adopts the inductive switch, which can move quickly and locate on the guide line, the fixation mechanism of screen frame also can be adjusted quickly, which reduce the time of exchanging frame and printing and increase the work efficiency.
6. There is snap-off device, and the height of snap-off can be adjusted, which ensure the printing precision and quality of products.
7. The run of whole machine is controlled by the microcomputer. The printing time and printing delay both can be adjusted and shown instantly. The speed of printing and ink returning can be adjusted quickly. There is the safe system of rising back urgently which to protect the safe of worker.

Technical Specifications

Model	JB-750II	JB-960II	JB-1280II
Max. printing size	500 x 700mm	600 x 900mm	800 x 1200mm
Max. frame size	800 x 1080mm	900 x 1150mm	1000 x 1580mm
Worktable size	600 x 900mm	700 x 1100mm	800 x 1400mm
Printing speed	1200pcs/h	1100pcs/h	900pcs/h
Overprint precision	≤ 0.10mm	≤ 0.10mm	≤ 0.10mm
Thickness	~ 40mm	~40mm	~40mm
Height of Instant off-network	0~20mm	0~20mm	0~20mm
Power	3P 380V 2.45KW	3P 380V 3.5KW	3P 380V 4.9KW
Total weight	600Kg	750Kg	900Kg
Overall dimensions	1.5 × 1.08 × 1.7m	1.5 × 1.18 × 1.7m	2 × 1.28 × 1.7m

Configuration List

No	Name	Qty	Manufacturer	Remark
1	PLC	1	Japan Omron	
2	Inverter	1	Japan MITSUBISHI	Printing
3	Inverter	1	MITSUBISHI	Up and down
4	Exhuast	1	Qiangli Motor	
5	Speed reducer	1	Ziguang	Printing

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

6	Speed reducer	1	Taiwan Liming	Up and down
7	Time relay	1	Japan Omron	
8	Counter	1	Japan Omron	
9	Hot relay	1	France Schneider	
10	AC relay	1	Schneider	
11	Micro-relay	5	Schneider	
12	Breaker	3	Schneider	
13	Press/knob button	6	Schneider	
14	Jiggle switch	4	Schneider	Return up
15	Emergency stop switch	1	Hongbo	
16	Small button	6	Hongbo	
17	On-off power	1	Taiwan Mingwei	
18	Inductive switch	4	H.W.L	Printing
19	Slot shape photo electricity	6	Japan Omron	Up and down exhaust
20	Cylinder	1	Japan SMC	Snap-off
21	Cylinder	1	Japan SMC	Blade-off
22	Cylinder	2	Japan SMC	Printing and ink reclaim
23	Electromagnetism	1	Japan SMC	Exhaust
24	Electromagnetism	3	Japan SMC	Printing/ink reclaim Snap-off
25	Gas and liquid changer	1	Japan SMC	
26	Link rod	1	Japan SMC	
27	Lead rail	2	Taiwan ABBA	Printing
28	In-phase belt	1	Italy MEGADYNE	

0II almost are the same, just dimension is different of some spare parts.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA