



Products Type:



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Machine Introduction

Features:

1. Mold can be changed, to meet many customers' requirements
2. Patented products.
3. The device has Full-featured, stable performance, environmental protection, low noise, easy to operate, easy to maintain.
4. Automatic power-off function to protect the safety of operating personnel.
5. Foot switch, hands free, more productive and higher pass rate.
6. Single heater pipe, single-control, low energy consumption.
7. Low-cost, less investment, it is the best choice for new starter
8. It can use as sample machine, easy to operate.
9. Two work station will improve the productivity
10. Simple operation, zero failure, maintenance-free, easy mold change, low price, easy to move, suitable for small batch production, proofing, small-scale, and new users.

Technical Specifications

Model	ZCJ-A
Rated productivity	24-30pcs/min (different type different productivity)
Raw material	150-360g/m ² PE/PLA coated paper
Molding temperature	160-200°C
Air pressure	0.5Mpa-0.8Mpa
Air flow volume	1m ³ /min
Total power	3.3kw
Electrical supply	220V 50Hz
Weight	250kg
Dimension	1530× 1100× 640mm
Mold	One set mold for free, extra mold will charge
Optional	Air compressor to supply air pressure
Max size of box	Width of unfold paper max is 360mm
Forming method	Heat sealing (heat pipe)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657





Machine Part Features

Machine Part	Features
	HIGH SPEED PRODUCTION EFFICIENCY Two work stations produce at the same time, save time, can produce different types of products at the same time, stable quality standards, high output, good efficiency.
	MULTI-FUNCTION EASY TO OPERATE Can replace the mold, easy to operate, easy to manufacture different specifications of products to produce it is the most economical solution.
	ONE BUTTON START UP CONTROL DISPLAY Key start, Chinese and English, temperature control table clearly display mold temperature, convenience and timely adjustment.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



	CYLINDER DEVICE Cylinder device, only 0.6-0.8 Mpa air pressure can meet the production.
	RELIABLE QUALITY OF ACCESSORIES Using high-quality accessories and drive system, pressure gauge pressure valve quality and reliable, stable performance, so that you can use peace of mind.
	ELECTRICAL CABINET FIGURE Yanggu wire, Jung-tae contactor, RKC Japan temperature control.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

