



### Machine Introduction

This machine is applicable to slitting of various roll materials such as BOPP, PET, CPP, CPE, PVC, etc., and trimming and slitting of materials according to different needs in the production process.

#### Features:

1. The machine adopts DC motor to maintain smooth operation during acceleration; (Variable frequency speed regulation can also be adopted)
2. Automatic meter counting, alarm, and other functions.
3. The winding adopts A and B air expansion shaft structure, which is convenient for loading and unloading.
4. Unwinding adopts photoelectric automatic deviation correction system to enable irregular materials to be cut normally
5. Automatic discharge device for flat knife slitting waste edge
6. Manual feeding, air expansion shaft (key bar type) 3 inches.

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



### Technical Specifications

|                                            |                                                                            |
|--------------------------------------------|----------------------------------------------------------------------------|
| <b>Model</b>                               | <b>LS-1600</b>                                                             |
| Width                                      | 1600                                                                       |
| Deviation                                  | ±0.5mm                                                                     |
| Cutting thickness                          | 20g-300g/m <sup>2</sup>                                                    |
| Cutting accuracy                           | ±0.5mm                                                                     |
| Speed                                      | 10-150m/min                                                                |
| Total power                                | 6.5kw                                                                      |
| Machine color                              | The body color is gray, and the cover is white (other colors are optional) |
| Automatic photoelectric correction         | depending on different raw materials and customer specific requirements)   |
| Maximum diameter of raw material unwinding | Φ500mm                                                                     |
| Maximum diameter of raw material rewind    | Φ500mm                                                                     |
| The maximum width of raw materials         | 1600mm                                                                     |
| Air shaft                                  | φ74mm                                                                      |
| Number of simultaneous rewind shafts       | 2 (single shaft reeling is allowed)                                        |
| weight                                     | 1600kg                                                                     |
| Overall size:                              | 1400x2700x1300mm                                                           |

### Part Specifications

#### 1. Unwinding Part:

|                                           |                                                          |
|-------------------------------------------|----------------------------------------------------------|
| The frame is of casting structure         | 120 # high quality casting structure, 45 * steel support |
| Magnetic particle tension control         | 10-100N.M                                                |
| Tension magnetic                          | Threading shaft Air expansion shaft: one set             |
| Photoelectric correction system           | correction accuracy: ± 0.5mm 1 set                       |
| Deviation correction                      | 110 type synchronous motor drive: one set                |
| Photoelectric eye for tracking correction | 1                                                        |
| Base material Manual operation            | Left right and parallel adjustment                       |
| Drive guide roller                        | aluminum guide rod is dynamically balanced               |

#### 2. Host Part:

##### Tow Device:

|                                                             |
|-------------------------------------------------------------|
| Structural type: active traction pneumatic compression type |
| The pressing mode is controlled by cylinder                 |
| Compression cylinder specification: φ 50 * 25 2 pcs         |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657



|                                                                                                                              |                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| The compression roller is rubber roller (specification: $\phi$ ninety $\times$ 1630mm) 1pc                                   |                                                                                                              |
| The driving roller adopts rubber roller (specification: $\phi$ one hundred and six $\times$ 1630mm)1pc                       |                                                                                                              |
| Drive mode: the main motor drives the main drive shaft, and the main shaft drives the driving roll for traction              |                                                                                                              |
| <b>The driving and transmission mechanism</b>                                                                                |                                                                                                              |
| The main motor actively adopts the combination of motor and variable speed wheel                                             |                                                                                                              |
| The main motor adopts a 5.5KW speed regulating motor, 1 set                                                                  |                                                                                                              |
| The frequency converter adopts Shenzhen Boteng Technology Co., Ltd. (5.5KW)                                                  |                                                                                                              |
| The transmission mechanism is a combination of pulley and chain                                                              |                                                                                                              |
| Guide roller: aluminum alloy guide roller is used for dynamic balancing                                                      |                                                                                                              |
| Aluminum guide roll hard oxidation specification: $\phi$ 80 1630mm                                                           |                                                                                                              |
| <b>Slitting Device</b>                                                                                                       |                                                                                                              |
| round knife structure                                                                                                        |                                                                                                              |
| 1pc upper and 1pc lower knife roll                                                                                           |                                                                                                              |
| 8 pairs of round tool rest                                                                                                   |                                                                                                              |
| <b>3. Rewinding device</b>                                                                                                   |                                                                                                              |
| Structure Mode                                                                                                               | Double air expansion shaft winding (or single shaft winding)                                                 |
| Unwind Diameter                                                                                                              | $\Phi$ 500mm                                                                                                 |
| clutch                                                                                                                       | 10KG                                                                                                         |
| compression type                                                                                                             | cylinder top sleeve structures and back pressure shaft devices 2pcs                                          |
| Transmission Mode                                                                                                            | Chain wheel drive<br>Tile type air expansion shaft (specification: $\phi$ seventy-four $\times$ 1550MM) 2pcs |
| <b>4. Waste disposal device</b>                                                                                              |                                                                                                              |
| Discharging mode:                                                                                                            | air blower, waste exhaust                                                                                    |
| Fan                                                                                                                          | three-phase asynchronous motor (specification: 0.55kw), 1 set                                                |
| <b>5. Control part</b>                                                                                                       |                                                                                                              |
| The control system of the machine can be roughly divided into three parts: host control, tension control and other controls. |                                                                                                              |
| Host control: plc + man-machine interface (taper tension)                                                                    |                                                                                                              |
| Tension control: unwinding tension, winding tension, control speed range is wide, excellent at low speed and high speed      |                                                                                                              |
| Good performance and excellent winding effect.                                                                               |                                                                                                              |
| With electronic meter counter; Alarm shutdown; Automatic length setting.                                                     |                                                                                                              |
| The machine can be shut down with preset cutting length                                                                      |                                                                                                              |
| <b>6. Supporting facilities: (user is responsible)</b>                                                                       |                                                                                                              |
| Power                                                                                                                        | three-phase four wire air switch: voltage 380V 50HZ                                                          |
| Air compressor                                                                                                               | 1.5KW                                                                                                        |

\* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



**PT. EKA MAJU MESININDO**  
Jl. Terusan Bandengan Utara No.16 / B 3-4  
Jakarta, 14450, Indonesia  
Tel. (021) 660 2665, 661 8255.  
Fax. (021) 668 5874, 660 2657

