



Machine Introduction

Function Description

Unwinding part

1. Adopts automatic cylinder loading. Magnetic brake. Automatic tension.
2. It does not need to input the material thickness, the proximity switch can inspect the unwinding diameter directly which near the transmission shaft. The machine can slow down according to the rest material, in this way, the worker can prepare for the next roller.
3. With the manual adjustment system, the unloading material tightness can be controlled. The adjustable range: $\pm 20\text{mm}$
4. Automatic error-correction for the edge position is controlled by the system. The whole frame adopts guide way type to move left and right which driven by servo motor. The moving part uses thread screw.
5. Corridor type feeding materials easily for operation.
6. Magnetic powder: 20KG, Brake: 1sets

Traction part

The 5.5 KW servo motor drives the mirror surface and pinch roll

Waste paper recycle device

Using motor to blow out the waste paper. The net cage should be prepared by customer.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657



Rewinding part (automatic loading and discharging, easily for operation)

1. Rewinding the cut material by upper and bottom double bearing.
2. Each rewinding shaft with 1 set of 7.5KW servo motor to drive the air shaft. The tension decided by the roll diameter. PLC controls SMC electric automatically to make all the sheet same thickness when do the multiple slitting. Because of the press roller, all the reels end face is smooth. it has the choice of pneumatic press roller and self-weight press roller. The screw type rewinding way can control the degree of the tightness of the finished products. With the increasing of the rewinding diameter, the servo motor speed goes down to extend the life of the air shaft. The air shaft never broken except the human factor
3. It can choose the whole shaft tension without friction and the servo motor in torque control mode in PLC

Rewinding and discharging: automatic up and down

Technical Specifications	
Model	WZFQ-1600A
Material type	For large rolling materials, such paper sticker, paper, compound printing paper and so on.
Material thickness	50-350g (paper)
Max. Diameter	1400mm
Paper roll	3" for choice
Max width	1600mm
Roller width	1650mm
Slitting width	30-1600mm
Rewinding paper roll	3"
Rewinding max. Diameter	1000mm
Error-correction	150mm
Precision	+/-0.15mm
Max. Speed	350m/min
Slitting speed	10-350m/min
Power	22 KW
Weight	4800KG
Dimension	Length: 3400, width 3100, height 1800mm
Slitting tolls	Standard for 15 sets, according to customer's requirement
Upper cutter	Φ125*85*1.2mm brand Shanghai
Bottom cutter	Φ100*20*16mm brand Shanghai
Rewinding shaft	2 pcs of 3"air shaft (6" for choice)
Equipment	With the Φ90 hard aluminum oxide guide roller

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Configurations

No	Name	Specification	Qty	Brand
1	45# steel frame	Thickness of wallboard 60mm	1set	Shanghai Baosteel
2	3" air adjust air shaft		2pcs	Ningbo
3	Main traction roll(mirror)	φ200*1650mm	1pcs	Hard chromium plating with glazing. Dynamic balance 500m/min. Precision G1.6
4	Rubber press roller	φ150*1650mm	1pcs	Imported silica gel, the hardness reach to 70degree, Dynamic balance 500m/min. Precision G1.6
5	Hardness aluminum oxide guide roller	φ90*1650mm	1	Hardness oxidation treatment, Dynamic balance 500m/min. Precision G1.6
6	Rewinding servo motor	7.5KW	2sets	zhima
7	Traction servo motor	5.5KW	1set	zhima
8	Unwinding pneumatic brake	20KG	1sets	Wenzhou
9	Motor for blowing the slitter edge	1.1KW	1	Wenzhou
10	Bearing		some	NSK HRB
11	Pneumatic part		some	huanhua
12	U Simulation error-correction		1set	ARISE
13	PLC	SIMATLC S7-200SMART	1pcs	SIEMENS
14	10" touch screen	TPC1061Ti	1pcs	MCGS
15	Proximity switch		1pcs	OMRON from Japan
16	Low-voltage apparatus		some	Schneider
17	Power supply	S100-24	1pcs	Taiwan meanwell



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

