



Machine Introduction

This machine is designed to manufacture square bottom paper bags from paper reel in blank or printed. Side gluing, tube forming, cutting, bottom impressing, bottom gluing, bottom forming and final product collection can be completed within one time by this machine. It is an ideal equipment for making paper bags for foodstuff bags. Controlled by PLC system, equipped with touch screen and servo motor for bag length control, this machine can produce paper bags of different sizes.

Features :

1. Touch screen is adopted for input control and machine status display, so as to finish machine correction easily.
2. Equipped with originally imported SIEMENS electrical system and servo motor drive, to make the machine run steadily.
3. Germany SICK photoelectric detector is used to track the material to be printed, reduce the adjusting time and improve production efficiency.
4. Separate single-station unwinding rollstand with hydraulic lifting device; Convex-type inflatable shaft for loading material (or shaftless loading); Magnetic powder brake for unwinding and automatically constant tension controller for unwinding tension control; EPC web guide control system for material alignment; alarm function for reminding replacing material and stopping-machine device for detecting material broken.
5. Adjustable forming mould structure (side sealing is above the forming mould); gluing pulley with automatic disengaging function is used for side gluing.
6. Rotary serrated cutter (or flat-blade cutter) with elliptical gears is used for cutting; the cutting length can be corrected by SICK photoelectric detector; Multi-layers bottom forming drum, center grippers, second tuck clamps, and drum grippers are adjustable for ease of changeover; automatic disengaging function (bottom gluing is prevented for empty feeding to avoid contamination to the surface of the drum).
7. Paper bags are delivered by belt, and collected at side workbench, which is easy for operations; automatic counting function.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA

Technical Specifications

Model	ZD-FJ18B
Paper roll width	660-1230 mm
Tube length	270-530 mm
Bag body width	260-450 mm
Paper thickness	60-180 gsm
Max. production speed	160 bags/min
Power	18.5 kw
Total Weight	Approx 10000 kg
Overall Dimensions	9000x3500 x1900 mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657

34 YEARS
SERVING
INDONESIA