




Machine Introduction

Equipment features and functions:

1. There are suction and wheel pressure under the paper feeding table.
2. Main engine wallboard cast iron structure, 6 paper inlet belts and 2 paper outlet belts with suction underneath.
3. The coating roller adopts the rolling extrusion oil and reverse oil (the latter is used when making dumb oil and tissue paper).
4. The paper feeding position is equipped with optical fiber probe for accurate memory of paper feeding.
5. The coating cots are equipped with optical fiber, in order to protect the cots, the paper will automatically stop.
6. Thin paper USES air knife to blow qigong energy, optical fiber and encoder to control solenoid valve.
7. The oven is equipped with a standard of 6 meters (customized according to customer requirements). The oven heating lid will automatically rise and fall when the machine is shut down or started up.
8. The mesh belt is high temperature resistant and automatic edge correction.
9. Part of the paper receiving machine: 6 strips of paper feeding belt (with suction) are pressed into corrugated form with the upper pressing wheel to improve the paper receiving effect, and there is qigong blowing energy below.
10. Diversified instrument display. (Can display presets, cumulative count; Meter, linear speed, efficiency, etc.)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications	
Model	CYSG-800M
Type	Paper feeder, main machine, drying path, paper feeder
Frequency	Taida
Paper weight	200g-600g
Low voltage	Schneider
Touch Screen	Taida
Solenoid valve	Yadeke
Bearing	NSK
Quartz tube	HONGDA
Blower	Chuangda
Motor	Shanghai
Tunnel	5000mm × 1pcs
Glue Barrel	1pcs
Glue Pump	1pcs
Glue dish	1pcs
	Closed circuit TV display, PUC control, linkage of whole machine.
Speed	5-30M/min
Max. paper size	800MM
Dryer way	IR/UV
IR Drying Tunnel	IR light 30-100°C power 1.5KW/18pcs
IR Fan	8pcs
IR Power	27KW
UV Tunnel	UV power 8KW/3pcs
Total Power	48kw
Weight	3000kg
Dimension	7600*1600*1550mm

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

